

# TA-ZJL19QX/RX

Full IP65 Fanless Industrial 5W / PCT Touch Monitor



## Feature

- Fanless design and compact solution
- Fully IP65 compliant 6-sided stainless steel chassis
- All IP65 waterproof stainless steel connectors
- 5-wire resistive / PCT touch screen
- 1 x VGA, 1 x USB or 1 x RS232 for touch screen
- No Touch Screen (optional)

I/O Ports	
VGA	1
USB or RS232	1
Display	
Size	19" TFT (4:3)
Backlight	LED
Resolution	1280 x 1024
Colors	16.7 M
Luminance ( cd/m2)	250
Contrast Ratio	1000:1
MTBF (hrs)	50,000
View Angle ( H / V )	170/160

Touch screen			
Touch screen	5-wire resistive / PCT		
OS Support			
Win 7 Pro, Embedded 7, Win XP Pro, Embedded XP			
Power Requirement			
Model Number	PCT	TA-ZJL19QF	TA-ZJL19QW
	5W	TA-ZJL19RF	TA-ZJL19RW
Power Input Voltage		DC in 12V (default)	DC in 19~36V (Optional)
Mechanical & Environmental			
Operation Temp		0°C~ 45°C	
Storage Humidity		10 ~ 90%, non-condensing	
Mount		VESA mount 100 x 100 mm	
Dimension (W x H x D, mm)		521.4 x 434.4 x 67.1	
Weight		11	
Optional			
No Touch Screen		1	