

# TA-ZJL12QX/RX

Full IP65 Fanless Industrial PCT/5W Touch Monitor



## Feature

- Fanless design and compact solution
- Fully IP65 compliant 6-sided stainless steel chassis
- All IP65 waterproof stainless steel connectors
- 5-wire resistive / PCT touch screen
- 1 x VGA, 1 x USB or 1 x RS232 for touch screen
- No Touch Screen (Optional )

I/O Ports		
VGA		1
USB or RS232		1
Display		
Size	12.1" TFT (4:3)	12.1" TFT (4:3)
Backlight	LED	LED
Resolution	800 x 600	1024 x 768
Colors	16.2M	16.2M
Luminance ( cd/m2)	450	450
Contrast Ratio	700	700
MTBF (hrs)	50,000	50,000
View Angle ( H / V )	160/160	160/160

Touch screen			
Touch screen	5-wire resistive / PCT		
OS Support			
Win 7 Pro, Embedded 7, Win XP Pro, Embedded XP			
Power Requirement			
Power Input Voltage	DC in 12V (default)	DC in 19~36V (Optional)	
Model Number	PCT	TA-ZJL12QF	TA-ZJL12QW
	5W	TA-ZJL12RF	TA-ZJL12RW
Mechanical & Environmental			
Operation Temp	0°C~ 45°C		
Storage Humidity	10 ~ 90%, non-condensing		
Mount	VESA mount 100 x 100 mm		
Dimension (W x H x D, mm)	TBD		
Weight	TBD		
Optional			
No Touch	1		