ACP-4000

Quiet 4U Rackmount Chassis with Visual & Audible Alarm Notification



Features

- Supports either an ATX motherboard or PICMG backplane with up to 15 slots
- Shock-resistant disk drive bay design holds up to three 5.25" and one 3.5" disk drives
- LED indicators and alarm notification for system fault detection
- Low noise system fans
- Built-in Intelligent System Module enables whole system fan control and remote manageability

Quiet

C E FCC ROHS

Specifications


		External		
Drive Bay	3.5"	1		
	5.25"	3		
Cooling	Fan	2 (12 cm / 85 CFM each)		
Cooling	Air Filter	Yes		
Front I/O Interfess	USB 2.0	2		
Front I/O Interface	PS/2	1		
	LED Indicators	Power, HDD, temperature, fan, and power voltage status		
Miscellaneous	Rear Panel	Backplane version: One 9-pin D-Sub opening		
	neal Fallel	Motherboard version: Five 9-pin D-Sub & one 68-pin SCSI openings		
Intelligent System	CPU/System fan speed , CPU/System temperature , motherboard voltage			
Module Remote	(Only selected Advantech MBs/CPU cards with SUSIAccess installed can fully enable these functions, check with Advantech local rep. for detailed			
Monitoring	information.)			
		Operating	Non-Operating	
	Temperature	0 ~ 40° C (32 ~ 104° F)	-20 ~ 60° C (-4 ~ 140° F)	
Environment	Humidity	10 ~ 85% @ 40° C, non-condensing 10 ~ 95% @ 40° C, non-condensing		
	Vibration (5 ~ 500 Hz)	1 Grms	2 G	
	Shock	10 G (with 11 ms duration, half sine wave)	30 G	
Dhysical Characteristics	Dimensions (W x H x D)	482 x 177 x 479 mm (19" x 7" x 18.9")		
Physical Characteristics	Weight	15.2 kg (33.5 lb)		

Front View





Two 85 CFM cooling fans



Ordering Information

Part Number	Description		
Backplane Version			
ACP-4000BP-00CE	Without power supply, with ATX switch		
ACP-4000BP-30CE	Bundled with PS8-300ATX-ZBE		
Motherboard Version	1		
ACP-4000MB-00CE	Without power supply, with ATX switch		
ACP-4000MB-30CE	Bundled with PS8-300ATX-ZBE		

Power Supply Options

(For detailed power supply specs, please refer to Chapter 13)

Part Number	80 Plus Grade	Wattage	Туре	Input
PS8-300ATX-ZBE	Bronze	300W	Single	AC 100 ~ 240 V (full range)
PS8-400ATX-ZE	Bronze	400W	Single	AC 100 ~ 240 V (full range)
PS8-500ATX-ZE	Bronze	500W	Single	AC 100 ~ 240 V (full range)
RPS8-350ATX-XE	Gold	350W	1+1 Redundant	AC 100 ~ 240 V (full range)
RPS8-500ATX-XE	Bronze	500W	1+1 Redundant	AC 100 ~ 240 V (full range)
PS-300ATX-DC48E	N/A	300W	Single	DC -48 V

Optional Accessories

Part Number	Description
1700006915	ATX 24P/20P + 4P + 8P 60cm cable (connecting from power supply to alarm board)
1700006917	Two Mini DIN (connect to MB) / 6P (connect to front I/O board) PS2 KB/Mouse cable
IDT-5230E	Mobile rack for converting dual 5.25" drive bays to three 3.5" SAS/SATA HDD trays

^{*} If users use AIMB-763 or 3rd party motherboard, they need to purchase 1700006915 or 1700006916 for the front voltage LEDs to function normally. And they also need to purchase 1700006917 to make front PS/2 function normally.

Spare Parts

-	
Part Number	Description
2130006147S000	Door filter 97.6 x 36.6 x 5 mm
2130004803S000	Fan filter 115 x 195 x 5 mm

^{*} If users use ASMB-820 or ASMB-822, they need to purchase 1700006915 for the front voltage LEDs to function normally.