

DW-NLL15RF

6th Gen Intel® Core™ Celeron / i3/i5

Wide temperature Full IP65 Stainless Steel Panel PC



Feature

- Fanless design and compact solution
- 6th Gen Intel® Core™ Celeron / i3/i5 CPU
- Powerful performance but low power consumption
- Wide temperature: -20°C ~ 60°C
- 5 wire resistive touch screen solution
- Fully IP65 compliant 6-sided stainless steel chassis
- 1 x optional VGA port
- 1 x VGA port (optional) for Celeron i3 i5 only

System	
CPU	6th Gen Intel® Core™ Celeron 3955U i3-6100U/i5-6300U
Memory	1 x 204-pin DDR3L 1600 MHz SODIMM up to 8 GB
H/W Monitor	
Watchdog Timer	256-Level Watchdog Timer
I/O Ports	
RS232	2
USB	1
GLAN	1
Storage	
Storage	1 x SATA 2.0 2.5" HDD/SSD
Expansion	
Mini-PCIe	1 x Full-size (one w/ mSATA) 1 x Half Size
Power Requirement	
Power Input Voltage	DC in 12V power adapter
Touch Screen	
Touch screen	5-wire resistive

Display	
Size	15" TFT (4:3)
Resolution	1024 x 768
Colors	16.2M
Luminance (cd/m2)	400
Contrast Ratio	500:1
View Angle (H / V)	160/160
Mechanical & Environmental	
Operation Temp	-20°C to 60°C
Storage Humidity	10 ~ 90%, non-condensing
Mount	VESA mounting(100X100mm)
Dimension (W x H x D mm) &Weight	380 x 290 x 67 (11kg)
Optional	
RS232/485/422	1
Second LAN	1
External antenna	1 or 2
Full65 Power Adapter	1
VGA Port	1

DW-NLL17RF

6th Gen Intel® Core™ Celeron / i3/i5

Wide temperature Full IP65 Stainless Steel Panel PC



Feature

- Fanless design and compact solution
- 6th Gen Intel® Core™ Celeron / i3/i5 CPU
- Powerful performance but low power consumption
- Wide temperature: -20°C ~ 60°C
- 5 wire resistive touch screen solution
- Fully IP65 compliant 6-sided stainless steel chassis
- 1 x optional VGA port
- 1 x VGA port (optional) for Celeron i3 i5 only

System	
CPU	6th Gen Intel® Core™ Celeron 3955U i3-6100U/i5-6300U
Memory	1 x 204-pin DDR3L 1600 MHz SODIMM up to 8 GB
H/W Monitor	
Watchdog Timer	256-Level Watchdog Timer
I/O Ports	
RS232	2
USB	1
GLAN	1
Storage	
Storage	1 x SATA 2.0 2.5" HDD/SSD
Expansion	
Mini-PCIe	1 x Full-size (one w/ mSATA) 1 x Half Size
Power Requirement	
Power Input Voltage	DC in 12V power adapter
Touch Screen	
Touch screen	5-wire resistive

Display	
Size	17" TFT (4:3)
Resolution	1280 x 1024
Colors	16.7 M
Luminance (cd/m2)	350
Contrast Ratio	1000:1
View Angle (H / V)	140/170
Mechanical & Environmental	
Operation Temp	-20°C ~ 60°C
Storage Humidity	10 ~ 90%, non-condensing
Mount	VESA mounting(100X100mm)
Dimension (W x H x D mm) &Weight	425 x 361 x 68 (14kgs)
Optional	
RS232/422/485	1
Second LAN	1
External antenna	1 or 2
Full IP65 Power Adapter	1
VGA Port	1

DW-NLL19RF

6th Gen Intel® Core™ Celeron / i3/i5

Wide temperature Full IP65 Stainless Steel Panel PC



Feature

- Fanless design and compact solution
- 6th Gen Intel® Core™ Celeron / i3/i5 CPU
- Powerful performance but low power consumption
- Wide temperature: -20°C ~ 60°C
- 5 wire resistive touch screen solution
- Fully IP65 compliant 6-sided stainless steel chassis
- 1 x optional VGA port
- 1 x VGA port (optional) for Celeron i3 i5 only

System	
CPU	6th Gen Intel® Core™ Celeron 3955U i3-6100U/i5-6300U
Memory	1 x 204-pin DDR3L SODIMM up to 8 GB
H/W Monitor	
Watchdog Timer	256-Level Watchdog Timer
I/O Ports	
RS232	2
GLAN	1
USB	1
Storage	
Storage	1 x SATA 2.0 2.5" HDD/SSD
Expansion	
Mini-PCIe	1 x Full-size (one w/ mSATA) 1 x Half Size
Power Requirement	
Power Input Voltage	DC in 12V power adapter
Touch Screen	
Touch screen	5-wire resistive

Display	
Size	19" TFT (4:3)
Resolution	1280 x 1024
Colors	16.7 M
Luminance (cd/m2)	350
Contrast Ratio	1000:1
View Angle (H / V)	160/150
Mechanical & Environmental	
Operation Temp	-20°C ~ 60°C
Storage Humidity	10 ~ 90%, non-condensing
Mount	VESA mounting(100X100mm)
Dimension (W x H x D mm) &Weight	455X367.6X67(15kgs)
Optional	
RS232/422/485	1
Second LAN	1
External antenna	1 or 2
Full IP65 Power Adapter	1
VGA Port	1