

DURALIGHT

10000000

16-16-16

ا(∞)(~)(∘

GENERAL TECHNICAL SPECIFICATIONS

IP67

: IP67 sealed

: 0°C to +60°C

Compass safe distance : 0.5m (panel mount) / 1.4m (enclosed)

I FD

: 92 short travel switches, tactile feel switches

: 50 mm laser trackball, epoxy resin ball

shielded cable of 1.8 meter.

scratch and chemical resistant

: Directly from USB port

: USB output for keyboard and trackball via

with 0,3 mm travel and 2,55 N operating force

: Black polyester front layer with embossed keys,

1 - 1 (-) (-)

MARINE KEYBOARDS & POINTING DEVICES

FOR THE MOST DEMANDING JOBS

BACKLIT KEYBOARDS

KSML92-W-MC1

IEC 60945 FULLY TESTED MARINE KEYBOARD

Compact LED backlit keyboard with removable 50mm laser trackball



This "Duralight" 92 key backlit keyboard is approved for use with Solas Marine applications (f.i ECDIS). The keyboard features a compact full MF keyboard with integrated numpad and a large 50mm laser trackball with removable ball.

MAIN FEATURES

- Certificate of Conformity fully compliant with IEC60945
- Compact layout
- Removable 50 mm laser trackball
- High brightness LED's with fibre optics
- Illumination of the key legends and contour, the trackball contour and even customer logo's or trademarks.
- . Low power LED's warrant for a long life
- No external power supply necessary, keyboard port power sufficient
- Dimmable backlighting at 8 levels by two dedicated keys
- Intelligent luminosity setting of "numlock" and capslock" LED's
- White backlighting as standard, other colours on request.

Panel mount version :

- Aluminium carrier and silicone sponge panel sealing
- Front panel mounting with holes (for countersunk M4 screws, not included)
- Added silicon sponge seal for perfect sealing into the user's panel
- The rear side components are protected by a covering metal plate
- Dimensions / weight : 385 x 185 x 50 mm / 1,2 kg

Enclosed version :

- The keyboard is mounted in a robust, all steel enclosure
- Industrial epoxy coating (mid-grey).
- Dimensions / weight : 418 x 246 x 70 mm / 3,5 kg

CUSTOMIZATION

Possible customization includes adapted backlighting controls, addition of company logo or specific function keys, different layouts, different colour, all this without having to reapply for certification!



ORDER INFO

L

Sealing

Pointing Device Output

Operating temp.

Front layer

Power requirements

Keys

AYOUT	

IEC60945 certificate_ksml92.pdf

PANEL MOUNT

ENCLOSED

US Qwerty	KSML92 F0001-W-MC1	KSML92 S0001-W-MC1
RU Cyrillic	KSML92 F0007-W-MC1	KSML92 S0007-W-MC1

USB output, white backlighting

VER. 1.0




MARINE KEYBOARDS & POINTING DEVICES FOR THE MOST DEMANDING JOBS

BACKLIT KEYBOARDS

KSML92-W-MC1

DIMENSIONAL DRAWING

panel mount version



The company reserves the right to alter without prior knowledge the specification or design of any standard product or service.



MARINE KEYBOARDS & POINTING DEVICES FOR THE MOST DEMANDING JOBS


BACKLIT KEYBOARDS

KSML92-W-MC1

DIMENSIONAL DRAWING







COLOURS Keyboard & Key Background : PANTONE Black 2 C 2X

Key edges & key legends : white translucent

The company reserves the right to alter without prior knowledge the specification or design of any standard product or service.