



EMC UPDATE TEST REPORT

For

Advantech Co., Ltd.

IPC

Model: IPC-623BP00XB-ES; IPC-623BP-46RZB;
**IPC-623BP-40ZB; **IPC-623BP-50ZB

Trade Name: ADVANTECH

Revision: 02

Description of Rev. 02:

1. Applicant adds two model numbers for differ Power Supply, the detail difference please refer to EUT Description (Page 3).
(Please refer to have ** mark items on this report)
2. Other information, please refer to the 50121110, 51017103 and this test report.

Approved by:

Reviewed by:

Kurt Chen
Director of Linkou Laboratory
Compliance Certification Services Inc.

Susan Su
Section Manager of Linkou Laboratory
Compliance Certification Services Inc.

Note: This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. Ltd. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document.



1 TEST RESULT CERTIFICATION

Applicant: Advantech Co., Ltd.
No. 1, Alley 20, Lane 26, Rueiguang Road, Neihu District,
Taipei 114, Taiwan, R.O.C.

Manufacturer: Advantech Co., Ltd.
No. 1, Alley 20, Lane 26, Rueiguang Road, Neihu District,
Taipei 114, Taiwan, R.O.C.

Equipment Under Test: IPC

Trade Name: ADVANTECH

Model: IPC-623BP00XB-ES; IPC-623BP-46RZB;
**IPC-623BP-40ZB; **IPC-623BP-50ZB

Detailed EUT Description: See Item 2 of this report

Applicable Standard	Class/Limit/Criterion	Test Result
EN 55022: 1998 + A1: 2000 + A2: 2003	Class A	N/A
EN 61000-3-2: 2000	Class D	N/A
EN 61000-3-3: 1995 + A1: 2001	Limit	N/A
EN 55024: 1998 + A1: 2001 + A2: 2003, including		
IEC 61000-4-2: 1995 + A1: 1998 + A2: 2000 EN 61000-4-2: 1995 + A1: 1998 + A2: 2001	Criterion B	N/A
IEC 61000-4-3: 2002 + A1: 2002 EN 61000-4-3: 2002 + A1: 2002	Criterion A	N/A
IEC 61000-4-4: 1995 + A1: 2000 + A2: 2001 EN 61000-4-4: 1995 + A1: 2001 + A2: 2001	Criterion B	N/A
IEC 61000-4-5: 1995 + A1: 2000 EN 61000-4-5: 1995 + A1: 2001	Criterion B	N/A
IEC 61000-4-6: 1996 + A1: 2000 EN 61000-4-6: 1996 + A1: 2001	Criterion A	N/A
IEC 61000-4-8: 1993 + A1: 2000 EN 61000-4-8: 1993 + A1: 2001	Criterion A	N/A
IEC 61000-4-11: 1994 + A1: 2000 EN 61000-4-11: 1994 + A1: 2001	Criterion B/C/C	N/A
Deviation from Applicable Standard		
1. According to applicant's declaration this EUT is a class A product, and to be market in industrial environment only. 2. The EN-Standards listed under EN 55024 are requested description by the applicant.		

The above equipment was tested by Compliance Certification Services Inc. for compliance with the requirements set forth in the EMC Directive 89/336/EEC, Amended by 92/31/EEC, 93/68/EEC and the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.



2 EUT DESCRIPTION

Product	IPC		
Trade Name	ADVANTECH		
Model	IPC-623BP00XB-ES; IPC-623BP-46RZB; **IPC-623BP-40ZB; **IPC-623BP-50ZB		
Housing Type	Metal Case		
EUT Power Rating	DCV From Power Supply		
Power Supply Manufacturer	Zippy	Model	HG2-6400P
			HP2-6500P
	EMACS	Model	RHI-6460P
Power Supply Power Rating	For HG2-6400P I/P: 100-240VAC, 63-47Hz, 8-4A O/P: +5VDC, 35A; -5VDC, 0.5A; +12VDC, 30A; -12VDC, 0.8A; +3.3VDC, 28A; +5VSB, 2.0A For HP2-6500P I/P: 115-240VAC, 47-63Hz, 8-4A O/P: +5VDC, 40A; -5VDC, 0.8A; +12VDC, 32A; -12VDC, 1.0A; +3.3VDC, 30A; +5VSB, 2.0A For RHI-6460P I/P: 100-240VAC, 47-63Hz, 8-4A O/P: +5VDC, 40A; -5VDC, 0-0.8A; +12VDC, 32A; -12VDC, 0-1A; +3.3VDC, 0-32A; +5VSB, 0-2A		
AC Power Cord Type	Unshielded, 1.8m (Detachable)		
CPU Manufacturer	Intel	Model	P4 3.2GHz
Memory Capacity	256MB		
HDD Manufacturer	Seagate	Model	ST340014A
FDD Manufacturer	TEAC	Model	FD-235HF
	NEC	Model	FD1231T
CD-ROM Manufacturer	Aopen	Model	CD-9501/TKC
			CD-950E/TKD
Chassis Manufacturer	ADVANTECH	Model	IPC-623
Backplane Manufacturer	ADVANTECH	Model	PCA-6116DP2
Main Board Manufacturer	ADVANTECH	Model	PCA-6119P7
CPU Board Manufacturer	ADVANTECH	Model	PCA-6186
VGA Manufacturer	On Board		
LAN Manufacturer	On Board		

**I/O Port of EUT (Type 1)**

I/O Port Type	Q'TY	TESTED WITH
1) Serial Port	1	1
2) PS/2 Keyboard / Mouse Port	1	1
3) Video Out Port (VGA)	1	1
4) LAN Port	1	1

I/O Port of EUT (Type 2)

I/O Port Type	Q'TY	TESTED WITH
1) Parallel Port	1	1
2) Serial Port	2	2
3) PS/2 Keyboard Port	1	1
4) PS/2 Mouse Port	1	1
5) Video Out Port (VGA)	1	1
6) LAN Port	2	2
7) USB Port	4	4
8) Earphone Port (On CD-ROM)	1	1

Note:

1. The difference between of two model numbers (list on this report) are identical, just for marketing purpose only.
2. Client consigns one model sample (Model number: IPC-623BP-46RZB) to test. Therefore, testing Lab. just guarantees the units, which have been tested.
- **3. The different between of four model numbers are list as below:

Model No.	Power Supply
IPC-623BP-46RZB; IPC-623BP00XB-ES	RHI-6460P
IPC-623BP-40ZB; IPC-623BP00XB-ES	HG2-6400P
IPC-623BP-50ZB	HP2-6500P



EMC UPDATE TEST REPORT

For

Advantech Co., Ltd.

IPC

Model: IPC-623BP00XB-ES; **IPC-623BP-46RZB

Trade Name: ADVANTECH

Date of Test: October 21 ~ November 29, 2005

Revision: 01

Description of Rev. 01:

1. Applicant adds one model number, just for marketing purpose only.
(Please refer to have ** mark items on this report)
2. Applicant adds one new appearance (Type 2) of EUT, the detail description please refer to Page 4 on this report.
(Please refer to have ** mark items on this report)
3. Applicant adds one Power Supply, one FDD, one ODD, one Main Board, one CPU Board of EUT and upgrades standard version for EN 55022 and EN 55024 to re-test
(Please refer to have ** mark items on this report)
4. Other information, please refer to the 50121110 and this test report.

Approved by:

Reviewed by:

Kurt Chen
Director of Linkou Laboratory
Compliance Certification Services Inc.

Susan Su
Section Manager of Linkou Laboratory
Compliance Certification Services Inc.

Note: This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. Ltd. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document.



TABLE OF CONTENTS

1	TEST RESULT CERTIFICATION	3
2	EUT DESCRIPTION.....	4
3	TEST METHODOLOGY	6
3.1	DECISION OF FINAL TEST MODE	6
4	SETUP OF EQUIPMENT UNDER TEST.....	7
5	INSTRUMENT AND CALIBRATION	8
5.1	MEASURING INSTRUMENT CALIBRATION.....	8
5.2	TEST AND MEASUREMENT EQUIPMENT	8
6	TEST RESULTS	11
7	POWER HARMONICS TEST	15
8	POWER VOLTAGE FLUCTUATION / FLICKER TEST	17
9	ELECTROSTATIC DISCHARGE (ESD) IMMUNITY TEST	19
10	RADIATED ELECTROMAGNETIC FIELD IMMUNITY TEST	24
11	FAST TRANSIENTS/BURST IMMUNITY TEST	27
12	SURGE IMMUNITY TEST	29
13	CONDUCTED DISTURBANCE/INDUCED RADIO-FREQUENCY FIELD IMMUNITY TEST	31
14	POWER FREQUENCY MAGNETIC FIELD IMMUNITY TEST	33
15	VOLTAGE DIPS / SHORT INTERRUPTIONS	35
	APPENDIX I - PHOTOGRAPHS OF TEST SETUP	37
	APPENDIX II – TEST RESULT OF EN 61000-3-2/-3	46



1 TEST RESULT CERTIFICATION

Applicant: Advantech Co., Ltd.
No. 1, Alley 20, Lane 26, Rueiguang Road, Neihu District,
Taipei 114, Taiwan, R.O.C.

Manufacturer: Advantech Co., Ltd.
No. 1, Alley 20, Lane 26, Rueiguang Road, Neihu District,
Taipei 114, Taiwan, R.O.C.

Equipment Under Test: IPC

Trade Name: ADVANTECH

Model: IPC-623BP00XB-ES; **IPC-623BP-46RZB

Detailed EUT Description: See Item 2 of this report

Date of Test: October 21 ~ November 29, 2005

Applicable Standard	Class/Limit/Criterion	Test Result
EN 55022: 1998 + A1: 2000 + A2: 2003	Class A	No non-compliance noted
EN 61000-3-2: 2000	Class D	No non-compliance noted
EN 61000-3-3: 1995 + A1: 2001	Limit	No non-compliance noted
EN 55024: 1998 + A1: 2001 + A2: 2003, including		
IEC 61000-4-2: 1995 + A1: 1998 + A2: 2000 EN 61000-4-2: 1995 + A1: 1998 + A2: 2001	Criterion B	No non-compliance noted
IEC 61000-4-3: 2002 + A1: 2002 EN 61000-4-3: 2002 + A1: 2002	Criterion A	No non-compliance noted
IEC 61000-4-4: 1995 + A1: 2000 + A2: 2001 EN 61000-4-4: 1995 + A1: 2001 + A2: 2001	Criterion B	No non-compliance noted
IEC 61000-4-5: 1995 + A1: 2000 EN 61000-4-5: 1995 + A1: 2001	Criterion B	No non-compliance noted
IEC 61000-4-6: 1996 + A1: 2000 EN 61000-4-6: 1996 + A1: 2001	Criterion A	No non-compliance noted
IEC 61000-4-8: 1993 + A1: 2000 EN 61000-4-8: 1993 + A1: 2001	Criterion A	No non-compliance noted
IEC 61000-4-11: 1994 + A1: 2000 EN 61000-4-11: 1994 + A1: 2001	Criterion B/C/C	No non-compliance noted
Deviation from Applicable Standard		
1. According to applicant's declaration this EUT is a class A product, and to be market in industrial environment only.		
2. The EN-Standards listed under EN 55024 are requested description by the applicant.		

The above equipment was tested by Compliance Certification Services Inc. for compliance with the requirements set forth in the EMC Directive 89/336/EEC, Amended by 92/31/EEC, 93/68/EEC and the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.



2 EUT DESCRIPTION

Product	IPC		
Trade Name	ADVANTECH		
Model	IPC-623BP00XB-ES; **IPC-623BP-46RZB		
Housing Type	Metal Case		
EUT Power Rating	DCV From Power Supply		
Power Supply Manufacturer	Zippy	Model	HG2-6400P
			HP2-6500P
	**EMACS	Model	RHI-6460P
Power Supply Power Rating	For HG2-6400P I/P: 100-240VAC, 63-47Hz, 8-4A O/P: +5VDC, 35A; -5VDC, 0.5A; +12VDC, 30A; -12VDC, 0.8A; +3.3VDC, 28A; +5VSB, 2.0A For HP2-6500P I/P: 115-240VAC, 47-63Hz, 8-4A O/P: +5VDC, 40A; -5VDC, 0.8A; +12VDC, 32A; -12VDC, 1.0A; +3.3VDC, 30A; +5VSB, 2.0A ** For RHI-6460P I/P: 100-240VAC, 47-63Hz, 8-4A O/P: +5VDC, 40A; -5VDC, 0-0.8A; +12VDC, 32A; -12VDC, 0-1A; +3.3VDC, 0-32A; +5VSB, 0-2A		
AC Power Cord Type	Unshielded, 1.8m (Detachable)		
CPU Manufacturer	Intel	Model	P4 3.2GHz
Memory Capacity	256MB		
HDD Manufacturer	Seagate	Model	ST340014A
FDD Manufacturer	TEAC	Model	FD-235HF
	**NEC	Model	FD1231T
CD-ROM Manufacturer	Aopen	Model	CD-9501/TKC
		**	CD-950E/TKD
Chassis Manufacturer	ADVANTECH	Model	IPC-623
Backplane Manufacturer	ADVANTECH	Model	PCA-6116DP2
**Main Board Manufacturer	ADVANTECH	Model	PCA-6119P7
**CPU Board Manufacturer	ADVANTECH	Model	PCA-6186
VGA Manufacturer	On Board		
LAN Manufacturer	On Board		

**I/O Port of EUT (Type 1)**

I/O Port Type	Q'TY	TESTED WITH
1) Serial Port	1	1
2) PS/2 Keyboard / Mouse Port	1	1
3) Video Out Port (VGA)	1	1
4) LAN Port	1	1

****I/O Port of EUT (Type 2)**

I/O Port Type	Q'TY	TESTED WITH
1) Parallel Port	1	1
2) Serial Port	2	2
3) PS/2 Keyboard Port	1	1
4) PS/2 Mouse Port	1	1
5) Video Out Port (VGA)	1	1
6) LAN Port	2	2
7) USB Port	4	4
8) Earphone Port (On CD-ROM)	1	1

Note:

1. The difference between of two model numbers (list on this report) are identical, just for marketing purpose only.
2. Client consigns one model sample (Model number: IPC-623BP-46RZB) to test. Therefore, testing Lab. just guarantees the units, which have been tested.



3 TEST METHODOLOGY

3.1 DECISION OF FINAL TEST MODE

1. The following test mode(s) were scanned during the preliminary test:

Mode 1

2048 × 1536 Resolution + RHI-6460P Power Supply + Quantum / ??? HDD + NEC / FD1231T FDD + Aopen / CD-950E/TKD CD-ROM + ADVANTECH / PCA-6119P7 Main Board + ADVANTECH / PCA-6186 CPU Board

Mode 2

1280 × 1024 Resolution + RHI-6460P Power Supply + Quantum / ??? HDD + NEC / FD1231T FDD + Aopen / CD-950E/TKD CD-ROM + ADVANTECH / PCA-6119P7 Main Board + ADVANTECH / PCA-6186 CPU Board

Mode 3

1024 × 768 Resolution + RHI-6460P Power Supply + Quantum / ??? HDD + NEC / FD1231T FDD + Aopen / CD-950E/TKD CD-ROM + ADVANTECH / PCA-6119P7 Main Board + ADVANTECH / PCA-6186 CPU Board

Mode 4

640 × 480 Resolution + RHI-6460P Power Supply + Quantum / ??? HDD + NEC / FD1231T FDD + Aopen / CD-950E/TKD CD-ROM + ADVANTECH / PCA-6119P7 Main Board + ADVANTECH / PCA-6186 CPU Board

2. After preliminary test, found mode 1 producing the highest emission level, used this mode for all final test.



4 SETUP OF EQUIPMENT UNDER TEST

Setup Diagram

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

Support Equipment

No.	Equipment	Model No.	Serial No.	FCC ID	Trade Name	Data Cable	Power Cord
1	Monitor	959NF	AQ19H2RT706121B	FCC DoC	SAMSUNG	Shielded, 1.8m with two cores	Unshielded, 1.8m
2	Modem	DM-1414	304012269	IFAXDM1415	ACEEX	Unshielded, 1.8m	Unshielded, 1.8m
3	Printer	STYLUS C60	DR3K041737	FCC DoC	EPSON	Unshielded, 1.8m	Unshielded, 1.8m
4	PS/2 Keyboard	Y-SP29	SYU30272823	FCC DoC	Logitech	Unshielded, 1.8m	N/A
5	PS/2 Mouse	M-S34	HCA25200436	DZL211029	Logitech	Unshielded, 1.8m	N/A
6	Mouse	M-MM43	LZE95250096	FCC DoC	Logitech	Unshielded, 1.8m	N/A
7	USB 2.0 External HDD	F12-UF	A0100214-43b0015	FCC DoC	TeraSys	Shielded, 1.8m	N/A
8	USB 2.0 External HDD	F12-UF	A0100214-43b0011	FCC DoC	TeraSys	Shielded, 1.8m	N/A
9	USB 2.0 External HDD	F12-UF	A0100214-43b0006	FCC DoC	TeraSys	Shielded, 1.8m	N/A
10	USB 2.0 External HDD	F12-UF	A0100214-43b0014	FCC DoC	TeraSys	Shielded, 1.8m	N/A
11	Multimedia Headset	Axis-301	N/A	FCC DoC	TeraSys	Unshielded, 1.8m	N/A
12	HUB (Remote)	DS104	N/A	FCC DoC	NERGEAR	LAN Cable: Unshielded, 10m LAN Cable: Unshielded, 0.1m	Unshielded, 1.8m
13	Notebook PC (Remote)	COMPAQ NC 4010	CNU441F8LV	FCC DOC	HP	LAN Cable: Unshielded, 10m	AC I/P: Unshielded, 1.8m DC O/P: Unshielded, 1.8m with a core

Note: All the above equipment/cables were placed in worse case positions to maximize emission signals during emission test.

Grounding: Grounding was in accordance with the manufacturer's requirements and conditions for the intended use.



5 INSTRUMENT AND CALIBRATION

5.1 MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated once a year or in accordance with the manufacturer's recommendations, and is traceable under the IEC 17025 to international or national standards. Equipment has been calibrated by accredited calibration laboratories.

5.2 TEST AND MEASUREMENT EQUIPMENT

The following list contains measurement equipment used for testing. The equipment conforms to the requirement of CISPR 16-1, ANSI C63.2 and other required standards.

Calibration of all test and measurement, including any accessories that may effect such calibration, is checked frequently to ensure the accuracy. Adjustments are made and correction factors are applied in accordance with the instructions contained in the respective manual.

Equipment Used for Emission Measurement

Conducted Emission Test Site # 4				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EMI Test Receiver	R&S	ESCS30	847793/012	12/27/2005
LISN	EMCO	3825/2	9003-1628	07/28/2006
LISN	R&S	ENV 4200	830326/016	03/30/2006

Note: The measurement uncertainty is less than $\pm 2.83\text{dB}$, which is evaluated as per the NAMAS NIS 81 and CISPR/A/291/CDV.

Open Area Test Site # 2				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	ADVANTEST	R3261A	21720279	N.C.R
EMI Test Receiver	R&S	ESVS10	834468/006	04/06/2006
Pre-Amplifier	HP	8447D	2944A08780	07/18/2006
Bilog Antenna	Sunol Sciences	JB1	A031605	04/22/2006
Turn Table	EMCO	2081-1.21	9709-1885	N.C.R
Antenna Tower	EMCO	2075-2	9707-2060	N.C.R
Controller	EMCO	2090	9709-1256	N.C.R
RF Switch	ANRITSU	MP59B	M76890	N.C.R
Site NSA	CCS	N/A	N/A	08/19/2006
Decoupling Network	FISCHER CUSTOM COMMUNICATION INC.	F-201-DCN-5-6MM	12	03/17/2006

Note: The measurement uncertainty is less than $\pm 3.36\text{dB}$, which is evaluated as per the NAMAS NIS 81 and CISPR/A/291/CDV.



Power Harmonic & Voltage Fluctuation/Flicker Measurement (EN 61000-3-2&-3-3)				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
HARMONICS SYSTEM	EMC-PARTNER	HARMONICS-1000	094	11/04/2006

Equipment Used for Immunity Measurement

ESD Test Site (IEC/EN 61000-4-2)				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
ESD Generator	EM TEST	P30C	0603-01	07/10/2006

Radiated Electromagnetic Field Immunity Test Site (IEC/EN 61000-4-3)				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
S.G.	R&S	SMY02	100094	08/09/2006
Power Meter	R&S	NRVD	837794/029	08/09/2006
Power Sensor	R&S	URV5-Z2	835640/015	08/09/2006
Power Sensor	R&S	URV5-Z2	835640/016	08/09/2006
Power Amplifier	ar	150W1000	300300	N.C.R

Fast Transients/Burst Test Site (IEC/EN 61000-4-4)				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EMC TEST SYSTEM	EMC-PARTNER	TRANSIENT-2000	754	09/07/2006
Clamp	HAEFELY TRENCH	093 506.1	080 421.13	N.C.R

Surge Immunity Test Site (IEC/EN 61000-4-5)				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Surge Tester	HAEFELY TRENCH	PSUGER 4010	583 334-71	08/30/2006



CS Test Site (IEC/EN 61000-4-6)				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
S.G.	R&S	SMY02	100094	08/09/2006
Power Meter	R&S	NRVD	837794/029	08/09/2006
Power Sensor	R&S	URV5-Z2	835640/015	08/09/2006
Power Sensor	R&S	URV5-Z2	835640/016	08/09/2006
Power Amplifier	ar	500A100A	300299	N.C.R
CDN	Lüthi	801-M3	1879	03/04/2006
CDN	FRANKONIA	CDN-M2	A3002010	08/02/2006
CDN	SCHAFFNER	T400	16906	12/29/2005

Power Frequency Magnetic Field Immunity Test Site (IEC/EN 61000-4-8)				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
TRIAX ELF Magnetic Field Meter	F.W.BELL	4090	9711	11/21/2006
Magnetic Field Tester	HAEFELY TRENCH	MAG 100.1	080 938-01	N.C.R

Voltage Dips/Short Interruption and Voltage Variation Immunity Test Site (IEC/EN 61000-4-11)				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Dips/Interruption and Variations Simulator	HAEFELY TRENCH	PLINE 1610	080 344-05	04/10/2006



6 TEST RESULTS

Line Conducted Emission

CCS Conduction Test 4

Job No.: 51017103

Date: 2005/10/22

Time: AM 11:29

Temp.(°C)/Hum.(%):23 °C / 59 %

Tested by: Bill Cheng

Standard: CISPR 22 / EN 55022 Class A

Power Source: 230 Vac / 50Hz

Measured Line: L1


Company: ADVANTECH

Product:

Model: IPC-623BP-46RZB

Test Mode: 1

final Graph



Freq. (MHz)	QP Reading	AV Reading	Corr. factor	QP Result	AV Result	QP Limit	AV Limit	QP Margin	AV Margin	Remark
0.153	51.810	46.830	10.200	62.010	57.030	79.000	66.000	-16.990	-8.970	PASS
0.390	50.530	34.480	10.200	60.730	44.680	79.000	66.000	-18.270	-21.320	PASS
0.541	45.650	30.820	10.292	55.942	41.112	73.000	60.000	-17.058	-18.888	PASS
0.930	39.320	31.450	10.214	49.534	41.664	73.000	60.000	-23.466	-18.336	PASS
5.731	40.900	36.060	10.573	51.473	46.633	73.000	60.000	-21.527	-13.367	PASS
11.234	41.400	34.570	11.223	52.623	45.793	73.000	60.000	-20.377	-14.207	PASS
22.545	37.410	27.450	12.055	49.465	39.505	73.000	60.000	-23.535	-20.495	PASS

L1 = Line One (Live Line)



CCS Conduction Test 4

Job No.: 51017103

Date: 2005/10/21

Time: PM 09:20

Temp.(°C)/Hum.(%):23 °C / 59 %

Tested by: Bill Cheng

Standard: CISPR 22 / EN 55022 Class A

Power Source: 230 Vac / 50Hz

Measured Line: L2


Company: ADVANTECH

Product:

Model: IPC-623BP-46RZB

Test Mode: 1

final Graph



Freq. (MHz)	QP Reading	AV Reading	Corr. factor	QP Result	AV Result	QP Limit	AV Limit	QP Margin	AV Margin	Remark
0.154	57.020	46.150	10.200	67.220	56.350	79.000	66.000	-11.780	-9.650	PASS
0.312	59.800	42.430	10.225	70.025	52.655	79.000	66.000	-8.975	-13.345	PASS
0.462	63.610	45.610	10.338	73.948	55.948	79.000	66.000	-5.052	-10.052	PASS
0.616	60.580	45.220	10.323	71.903	55.543	73.000	60.000	-2.097	-4.457	PASS
1.005	54.370	40.730	10.400	64.770	51.130	73.000	60.000	-8.230	-8.870	PASS
5.730	45.730	41.150	10.500	56.230	51.650	73.000	60.000	-16.770	-8.350	PASS
14.178	55.360	48.530	11.251	66.611	57.781	73.000	60.000	-6.389	-2.219	PASS

L2 = Line Two (Neutral Line)

**Radiated Emission (A)****Model:** IPC-623BP-46RZB**Test Mode:** Mode 1**Temperature:** 21°C**Humidity:** 56% RH**Detector Function:** Quasi-peak.**Antenna:** Vertical at 10m**Tested by:** Harry Wang**Test Results:** Pass

(The chart below shows the highest readings taken from the final data)

Freq. (MHz)	Raw Data (dBuV)	Corr. Factor (dB/m)	Emiss. Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)
63.90	48.27	-17.32	30.95	40.00	-9.05
200.00	45.88	-10.48	35.40	40.00	-4.60
366.30	48.18	-6.78	41.40	47.00	-5.60
432.00	44.95	-5.50	39.45	47.00	-7.55
598.30	33.49	-2.32	31.17	47.00	-15.83
826.00	30.14	2.08	32.22	47.00	-14.78
987.10	26.95	5.50	32.45	47.00	-14.55

**Radiated Emission (B)****Model:** IPC-623BP-46RZB**Test Mode:** Mode 1**Temperature:** 21°C**Humidity:** 56% RH**Detector Function:** Quasi-peak.**Antenna:** Horizontal at 10m**Tested by:** Harry Wang**Test Results:** Pass

(The chart below shows the highest readings taken from the final data)

Freq. (MHz)	Raw Data (dBuV)	Corr. Factor (dB/m)	Emiss. Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)
34.60	38.21	-8.01	30.20	40.00	-9.80
116.00	41.94	-11.22	30.72	40.00	-9.28
125.60	41.15	-10.50	30.65	40.00	-9.35
232.60	40.61	-11.44	29.17	47.00	-17.83
333.10	41.16	-7.56	33.60	47.00	-13.40
432.00	43.10	-5.50	37.60	47.00	-9.40
598.30	30.94	-2.32	28.62	47.00	-18.38
733.00	29.57	1.23	30.80	47.00	-16.20
855.60	28.65	3.10	31.75	47.00	-15.25
992.70	26.10	5.75	31.85	47.00	-15.15



7 POWER HARMONICS TEST

Port : AC mains

Basic Standard : EN 61000-3-2 (2000)

Limits : ☐ CLASS A ; ☐ CLASS B ; ☐ CLASS C ; ☒ CLASS D


Tested by : Ethan Huang

Temperature : 22°C

Humidity : 53% RH

Limit:

Limits for Class A equipment		Limits for Class D equipment		
Harmonics Order n	Max. permissible harmonics current A	Harmonics Order n	Max. permissible harmonics current per watt mA/W	Max. permissible harmonics current A
Odd harmonics		Odd Harmonics only		
3	2.30	3	3.4	2.30
5	1.14	5	1.9	1.14
7	0.77	7	1.0	0.77
9	0.40	9	0.5	0.40
11	0.33	11	0.35	0.33
13	0.21	13	0.30	0.21
15<=n<=39	0.15x15/n	15<=n<=39	3.85/n	0.15x15/n
Even harmonics				
2	1.08			
4	0.43			
6	0.30			
8<=n<=40	0.23x8/n			

Block Diagram of Test Setup:**Test Procedure:**

- a. The EUT was placed on the top of a wooden table 0.8 meters above the ground and operated to produce the maximum harmonic components under normal operating conditions for each successive harmonic component in turn.
- b. The correspondent test program of test instrument to measure the current harmonics emanated from EUT is chosen. The measure time shall be not less than the time necessary for the EUT to be exercised.

Test Result : (See Appendix II for details)**PASS****FAIL**


8 POWER VOLTAGE FLUCTUATION / FLICKER TEST

Port : AC mains
Basic Standard : EN 61000-3-3 (1995 + A1: 2001)
Limits : §5 of EN 61000-3-3
Tested by : Ethan Huang
Temperature : 22°C
Humidity : 53%RH

Limit:

TEST ITEM	LIMIT	REMARK
P_{st}	1.0	P_{st} means short-term flicker indicator.
P_{lt}	0.65	P_{lt} means long-term flicker indicator.
T_{dt} (ms)	500	T_{dt} means maximum time that dt exceeds 3 %.
d_{max} (%)	4%	d_{max} means maximum relative voltage change.
dc (%)	3.3%	dc means relative steady-state voltage change

Block Diagram of Test Setup:



Test Procedure:

- a. The EUT was placed on the top of a wooden table 0.8 meters above the ground and operated to produce the most unfavorable sequence of voltage changes under normal operating conditions.
- b. During the flick measurement, the measure time shall include that part of whole operation cycle in which the EUT produce the most unfavorable sequence of voltage changes. The observation period for short-term flicker indicator is 10 minutes and the observation period for long-term flicker indicator is 2 hours.

Test Result: (See Appendix II for details)**Continue**

Test Parameter	Measurement Value	Limit	Result
P _{st}	0.072	1.0	Pass
P _{lt}	0.072	0.65	Pass
T _{dt} (ms)	0	500	Pass
d _{max} (%)	0%	4%	Pass
dc (%)	0.03%	3.3%	Pass

Manual Switch


Test Parameter	Measurement Value	Limit	Result
P _{st}	0.074	1.0	Pass
P _{lt}	0.074	0.65	Pass
T _{dt} (ms)	0	500	Pass
d _{max} (%)	0%	4%	Pass
dc (%)	0.05%	3.3%	Pass

9 ELECTROSTATIC DISCHARGE (ESD) IMMUNITY TEST

Port	: Enclosure
Basic Standard	: IEC/EN 61000-4-2
Test Level	: ± 8 kV (Air Discharge) ± 4 kV (Contact Discharge) ± 4 kV (Indirect Discharge)
Performance Criterion	: B (Standard Required)
Tested by	: Ethan Huang
Temperature	: 22°C
Humidity	: 53% RH
Pressure	: 1011mbar

Block Diagram of Test Setup:

(The 470 k ohm resistors are installed per standard requirement.)



Test Procedure:

1. The EUT was located 0.1 m minimum from all side of the HCP.
2. The indirect support units were located 1 m minimum away from the EUT, but direct support unit was/were located at same location as EUT on the HCP and keep at a distance of 10 cm with EUT.
3. A scroll 'H' test program was loaded and executed in Windows XP mode.
4. The Host PC sent above message to EUT and related peripherals through the test.
5. Active the communication function if the EUT with such port(s).
6. As per the requirement of EN 55024; applying direct contact discharge at the sides other than front of EUT at minimum 50 discharges (25 positive and 25 negative) if applicable, can't be applied direct contact discharge side of EUT then the indirect discharge shall be applied. One of the test points shall be subjected to at least 50 indirect discharge (contact) to the front edge of horizontal coupling plane.
7. Other parts of EUT where it is not possible to perform contact discharge then selecting appropriate points of EUT for air discharge, a minimum of 10 single air discharges shall be applied.
8. The application of ESD to the contact of open connectors is not required.
9. The EUT direct connection units also need to be applied ESD at the port of EUT cable connected.
10. Putting a mark on EUT to show tested points. The following test condition was followed during the tests.

Note: As per IEC/EN 61000-4-2, two 470k bleed resistors cable is connected between the EUT and HCP during the test applicable for power ungrounded or battery operating unit only.

The electrostatic discharges were applied as follows:

Amount of discharge	Voltage	Coupling	Result (Pass/Fail)
Mini 10 /Point	± 8 kV	Air Discharge	Pass
Mini 25 /Point	± 4 kV	Contact Discharge	Pass
Mini 25 /Point	± 4 kV	Indirect Discharge HCP	Pass
Mini 25 /Point	± 4 kV	Indirect Discharge VCP (Right)	Pass
Mini 25 /Point	± 4 kV	Indirect Discharge VCP (Left)	Pass

For the tested points to EUT, please refer to attached page.

(Blue arrow mark for Contact Discharge and red arrow mark for Air Discharge)



Performance & Result:

- ☒ **Criteria A:** The apparatus continues to operate as intended. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance.
- ☐ **Criteria B:** The apparatus continues to operate as intended after the test. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance. During the test, degradation of performance is however allowed.
- ☐ **Criteria C:** Temporary loss of function is allowed, provided the functions self recoverable or can be restored by the operation of controls.

☒ **PASS** ☐ **FAIL**

Observation: No function degraded during the tests.

The Tested Points of EUT

Photo 1 of 4



Photo 2 of 4





Photo 3 of 4




Photo 4 of 4



10 RADIATED ELECTROMAGNETIC FIELD IMMUNITY TEST

Port	: Enclosure
Basic Standard	: IEC/EN 61000-4-3
Requirements	: 10V/m / with 80% AM. 1kHz Modulation. (Customer Required)
Performance Criterion	: A (Standard Required)
Tested by	: Ethan Huang
Temperature	: 21°C
Humidity	: 51% RH
Pressure	: 1011mbar

Block Diagram of Test Setup:



Test Procedure:

1. The EUT was located at the edge of supporting table keep 3 meter away from transmitting antenna, it just the calibrated square area of field uniformity. The support units were located outside of the uniformity area, but the cable(s) connected with EUT were exposed to the calibrated field as per IEC/EN 61000-4-3.
2. Setting the testing parameters of RS test software per IEC/EN 61000-4-3.
3. Performing the pre-test at each side of with double specified level (6V/m) at 4% steps.
4. From the result of pre-test in step 5, choice the worst side of EUT for final test from 80 MHz to 1000 MHz at 1% steps.
5. Recording the test result in following table.
6. It is not necessary to perform test as per annex A of EN 55024 if the EUT doesn't belong to ITE product.

Preliminary test conditions:

Test level : 10V/m
Steps : 4 % of fundamental
Dwell Time : 3 sec

Range (MHz)	Field	Modulation	Polarity	Position	Result (Pass/Fail)
80-1000	10V/m	Yes	H	Front	Pass
80-1000	10V/m	Yes	V	Front	Pass
80-1000	10V/m	Yes	H	Right	Pass
80-1000	10V/m	Yes	V	Right	Pass
80-1000	10V/m	Yes	H	Back	Pass
80-1000	10V/m	Yes	V	Back	Pass
80-1000	10V/m	Yes	H	Left	Pass
80-1000	10V/m	Yes	V	Left	Pass

Final test conditions:

Test level : 10V/m
Steps : 1 % of fundamental
Dwell Time : 3 sec

Range (MHz)	Field	Modulation	Polarity	Position	Result (Pass/Fail)
80-1000	10V/m	Yes	H	Back	Pass
80-1000	10V/m	Yes	V	Back	Pass



Performance & Result:

- ☒ **Criteria A:** The apparatus continues to operate as intended. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance.
- ☐ **Criteria B:** The apparatus continues to operate as intended after the test. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance. During the test, degradation of performance is however allowed.
- ☐ **Criteria C:** Temporary loss of function is allowed, provided the functions self recoverable or can be restored by the operation of controls.



PASS




FAIL

Observation: No function degraded during the tests.

11 FAST TRANSIENTS/BURST IMMUNITY TEST

Port	: On Power Supply Line and LAN Cable
Basic Standard	: IEC/EN 61000-4-4
Requirements	: ± 2 kV for Power Supply Line (Customer Required) ± 1 kV for LAN Cable (Customer Required)
Performance Criteria	: B (Standard Required)
Tested by	: Ethan Huang
Temperature	: 22°C
Humidity	: 53% RH
Pressure	: 1011mbar

Block Diagram of Test Setup:



Test Procedure:

1. The EUT and support units were located on a wooden table 0.8 m away from ground reference plane.
2. A 1.0 meter long power cord was attached to EUT during the test.
3. The length of communication cable between communication port and clamp was keeping within 1 meter.
4. Injected test voltage to the EUT ports from minimum to standard request or client request.
5. Recording the test result as shown in following table.

**Test conditions:**

Impulse Frequency : 5kHz
Tr/Th : 5/50ns
Burst Duration : 15ms
Burst Period : 3Hz

Inject Line	Voltage kV	Inject Method	Result (Pass/Fail)
L	± 2	Direct	Pass
N	± 2	Direct	Pass
PE	± 2	Direct	Pass
L + N	± 2	Direct	Pass
L + PE	± 2	Direct	Pass
N + PE	± 2	Direct	Pass
L + N + PE	± 2	Direct	Pass
RJ 45 Port (LAN Cable)	± 1	Clamp	Pass

Performance & Result:

- ☒ **Criteria A:** The apparatus continues to operate as intended. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance.
- ☐ **Criteria B:** The apparatus continues to operate as intended after the test. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance. During the test, degradation of performance is however allowed.
- ☐ **Criteria C:** Temporary loss of function is allowed, provided the functions self recoverable or can be restored by the operation of controls.

**PASS****FAIL**

Observation: No function degraded during the tests.

12 SURGE IMMUNITY TEST

Port : Power Cord and LAN Cable

Basic Standard : IEC/EN 61000-4-5

Requirements : ± 1 kV (Line to Line)
 ± 2 kV (Line to Ground)

Performance Criteria : B (Standard Required)


Tested by : Ethan Huang

Temperature : 22°C

Humidity : 53% RH

Pressure : 1011mbar

Block Diagram of Test Setup:



Test Procedure:

1. The EUT and support units were located on a wooden table 0.8 m away from ground floor.
2. Injected test voltage to the EUT ports from minimum to standard request or client request.
3. Recording the test result as shown in following table.

**Test conditions:**

Voltage Waveform : 1.2/50 μ s
Current Waveform : 8/20 μ s
Polarity : Positive/Negative
Phase angle : 0°, 90°, 270°
Number of Test : 5

Coupling Line	Voltage (kV)	Polarity	Coupling Method	Result (Pass/Fail)
L1-L2	1	Positive	Capacitive	Pass
L1-PE	2	Positive	Capacitive	Pass
L2-PE	2	Positive	Capacitive	Pass
L1-L2	1	Negative	Capacitive	Pass
L1-PE	2	Negative	Capacitive	Pass
L2-PE	2	Negative	Capacitive	Pass

Performance & Result:

- ☒ **Criteria A:** The apparatus continues to operate as intended. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance.
- ☐ **Criteria B:** The apparatus continues to operate as intended after the test. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance. During the test, degradation of performance is however allowed.
- ☐ **Criteria C:** Temporary loss of function is allowed, provided the functions self recoverable or can be restored by the operation of controls.

**PASS****FAIL**


Observation: No function degraded during the tests.

13 CONDUCTED DISTURBANCE/INDUCED RADIO-FREQUENCY FIELD IMMUNITY TEST


Port	: AC Port and LAN Cable
Basic Standard	: IEC/EN 61000-4-6
Requirements	: 10V with 80% AM. 1kHz Modulation. (Customer Required)
Injection Method	: CDN-M3 for Power Cord CDN-T4 for LAN Cable
Performance Criterion	: A (Standard Required)
Tested by	: Ethan Huang
Temperature	: 21°C
Humidity	: 51% RH
Pressure	: 1011mbar

Block Diagram of Test Setup:

Side View:



Top View:



**Test Procedure:**

1. The EUT and support units were located at a ground reference plane with the interposition of a 0.1 m thickness insulating support and the CDN was located on GRP directly.
2. Setting the testing parameters of CS test software as per IEC/EN 61000-4-6.
3. Recording the test result in following table.

Test conditions:

Frequency Range : 0.15MHz-80MHz

Frequency Step : 1% of fundamental

Dwell Time : 3 sec

Range (MHz)	Field	Modulation	Result (Pass/Fail)
0.15-80	10V	Yes	Pass

Performance & Result:

- ☒ **Criteria A:** The apparatus continues to operate as intended. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance.
- ☐ **Criteria B:** The apparatus continues to operate as intended after the test. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance. During the test, degradation of performance is however allowed.
- ☐ **Criteria C:** Temporary loss of function is allowed, provided the functions self recoverable or can be restored by the operation of controls.

☒ **PASS** ☐ **FAIL****Observation:** No function degraded during the tests.

14 POWER FREQUENCY MAGNETIC FIELD IMMUNITY TEST

Port : Enclosure

Basic Standard : IEC/EN 61000-4-8

Requirements : 30 A/m (Customer Required)

Performance Criterion : A (Standard Required)


Tested by : Ethan Huang

Temperature : 22°C

Humidity : 53% RH

Pressure : 1011mbar

Block Diagram of Test Setup:



Test Procedure:

1. The EUT and support units were located on Ground Reference Plane with the interposition of a 0.1 m thickness insulation support.
2. Putting the induction coil on horizontal direction. (X direction)
3. Rotating the induction coil by 90° (Y direction)
4. Rotating the induction coil by 90° again (Z direction)
5. Recording the test result as shown in following table.

**Test conditions:**

Field Strength: 30A/m

Power Freq.: 50Hz

Orientation: X, Y, Z

Orientation	Field	Result (Pass/Fail)	Remark
X	30A/m	Pass	
Y	30A/m	Pass	
Z	30A/m	Pass	

Performance & Result:

- ☒ **Criteria A:** The apparatus continues to operate as intended. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance.
- ☐ **Criteria B:** The apparatus continues to operate as intended after the test. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance. During the test, degradation of performance is however allowed.
- ☐ **Criteria C:** Temporary loss of function is allowed, provided the functions self recoverable or can be restored by the operation of controls.

☒ **PASS** ☐ **FAIL****Observation:** No function degraded during the tests.

15 VOLTAGE DIPS / SHORT INTERRUPTIONS

Port : AC mains

Basic Standard : IEC/EN 61000-4-11

Requirement : PHASE ANGLE 0, 45, 90, 135, 180, 225, 270, 315 degrees

Voltage Dips	Test Level % U_T	Reduction (%)	Duration (periods)	Performance Criteria
	<5	>95	0.5	B
	70	30	25	C

Voltage Interceptions	Test Level % U_T	Reduction (%)	Duration (periods)	Performance Criteria
	<5	>95	250	C

Test Interval : Min. 10 sec.


Tested by : Ethan Huang

Temperature : 22°C

Humidity : 53% RH

Pressure : 1011mbar

Block Diagram of Test Setup:



Test Procedure:

1. The EUT and support units were located on a wooden table, 0.8 m away from ground floor.
2. Setting the parameter of tests and then Perform the test software of test simulator.
3. Conditions changes to occur at 0 degree crossover point of the voltage waveform.
4. Recording the test result in test record form.
5. Removes the Battery Pack to test if any.

**Test conditions**

The duration with a sequence of three dips/interruptions with interval of 10 s minimum
(Between each test event)

Voltage Dips:

Test Level % U _T	Reduction (%)	Duration (periods)	Observation	Meet Performance Criteria
0	100	0.5	Normal	A
70	30	25	Normal	A

Voltage Interruptions:

Test Level % U _T	Reduction (%)	Duration (periods)	Observation	Meet Performance Criteria
0	100	250	EUT shut down but can be recovered by manual, as the events disappear.	C

Normal: No any functions degrade during and after the test.

Performance & Result:

Criteria A: The apparatus continues to operate as intended. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance.

Criteria B: The apparatus continues to operate as intended after the test. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance. During the test, degradation of performance is however allowed.

Criteria C: Temporary loss of function is allowed, provided the functions self recoverable or can be restored by the operation of controls.

☒ **PASS** ☐ **FAIL**

APPENDIX I - PHOTOGRAPHS OF TEST SETUP

LINE CONDUCTED EMISSION TEST (EN 55022)



RADIATED EMISSION TEST (EN 55022)

POWER HARMONIC & VOLTAGE FLUCTUATION / FLICKER TEST



ELECTROSTATIC DISCHARGE TEST



RADIATED ELECTROMAGNETIC FIELD TEST



FAST TRANSIENTS/BURST TEST

SURGE IMMUNITY TEST



CONDUCTED DISTURBANCE, INDUCED BY RADIO-FREQUENCY FIELDS TEST



POWER FREQUENCY MAGNETIC FIELD IMMUNITY TEST



VOLTAGE DIPS / INTERRUPTION TEST





APPENDIX II – TEST RESULT OF EN 61000-3-2/-3

Harmonic Emission - IEC 61000-3-2 , EN 61000-3-2 , (EN60555-2)

Comply: IEC 61000-3-2 Ed.2.1 :2001 (incl. Amd.14) - IEC 61000-4-7 Ed.1.0 :1991

ADVANTECH

HARCS Setup File : [unnamed](#)


HARCS Report File : [unnamed](#)

Operator : Ethan Huang

EUT : IPC

Model No : IPC-623BP-46RZB

Remarks : TEMP:22 HUMD:53



Harmonic Emission - IEC 61000-3-2 , EN 61000-3-2 , (EN60555-2)

2005/10/21 下午 01:2

U _{rms} =	230.3	V	P =	147.2	W	THC =	0.155	A	Range:	2 A
I _{rms} =	0.720	A	pf =	0.888		P _{max} =	150.2	W	V-nom:	230 V
									TestTime:	5 min (100%)

IPC

Test completed, Result: PASSED

TEMP:22 HUMD:53

HAR-1000 EMC-Pictur

Full Bar : Actual Values

Empty Bar : Maximum Values

Blue : Current , Green : Voltage , Red : Failed

**Measurement**

ADVANTECH

Date : 2005/10/21 01:2 V4.10

File :

Operator : Ethan Huang
EUT : IPC
Model No : IPC-623BP-46RZB
Remarks TEMP:22 HUMD:53

Urms = 230.3V Freq = 49.987 Range: 2 A
Irms = 0.720A Ipk = 1.456A cf = 2.023
P = 147.2W S = 165.8VA pf = 0.888
THDi = 21.6 % THDu = 0.10 % Class D

Test - Time : 5min (100 %)

Limit Reference: Pmax = 150.15W

Test completed, Result: PASSED

Order	Freq. [Hz]	I _{max} [A]	I _{max} % [%]	I _{max} %L [%]	Limit [A]	Status
1	50	0.7145	99.271			
2	100	0.0045	0.6275			
3	150	0.1439	19.997	28.191	0.5105	
4	200	0.0021	0.2883			
5	250	0.0543	7.5475	19.040	0.2853	
6	300	0.0013	0.1866			
7	350	0.0084	1.1703	5.6094	0.1502	
8	400	0.0006	0.0848			
9	450	0.0138	1.9166	18.373	0.0751	
10	500	0.0011	0.1526			
11	550	0.0116	1.6113	22.066	0.0526	
12	600	0.0018	0.2544			
13	650	0.0143	1.9844	32.117	0.0445	



14	700	0.0018	0.2544		
15	750	0.0166	2.3066	43.076	0.0385
16	800	0.0017	0.2374		
17	850	0.0264	3.6635	77.538	0.0340
18	900	0.0015	0.2035		
19	950	0.0194	2.6967	63.791	0.0304
20	1000	0.0013	0.1866		
21	1050	0.0107	1.4925	39.022	0.0275
22	1100	0.0010	0.1357		
23	1150	0.0076	1.0516	30.111	0.0251
24	1200	0.0011	0.1526		
25	1250	0.0049	0.6784	21.116	0.0231
26	1300	0.0011	0.1526		
27	1350	0.0074	1.0346	34.778	0.0214
28	1400	0.0010	0.1357		
29	1450	0.0095	1.3229	47.764	0.0199
30	1500	0.0009	0.1187		
31	1550	0.0085	1.1872	45.822	0.0186
32	1600	0.0011	0.1526		
33	1650	0.0066	0.9159	37.629	0.0175
34	1700	0.0011	0.1526		
35	1750	0.0043	0.5936	25.867	0.0165
36	1800	0.0010	0.1357		
37	1850	0.0031	0.4240	19.532	0.0156
38	1900	0.0009	0.1187		
39	1950	0.0027	0.3731	18.117	0.0148
40	2000	0.0006	0.0848		



ADVANTECH

Date : 2005/10/21 PM 01:4 V4.10

File :

Operator : Ethan Huang
EUT : IPC
Model No : IPC-623BP-46RZB
Remarks TEMP:22 HUMD:53 (Continue)

Urms = 230.3V Freq = 49.974 Range: 2 A
Irms = 0.721A Ipik = 1.452A cf = 2.015
P = 147.3W S = 166.0VA pf = 0.887

Test - Time : 1 x 10min = 10min (100 %)

LIN (Line Impedance Network) : SLIN 0.24ohm +j0.15ohm N:0.16ohm +j0.10ohm

Limits :Plt : 0.65Pst : 1.00
dmax : 4.00 % dc : 3.30 %
dtLim: 3.30 % dt>Lim: 500ms

Test completed, Result: PASSED

Plt = 0.072

	Pst	dmax	dc	dt>Lim	Fail
		[%]	[%]	[ms]	
1	0.072	0.000	0.030	0.000	



ADVANTECH

Date : 2005/10/21 PM 01:5 V4.10

File :

Operator : Ethan Huang
EUT : IPC
Model No : IPC-623BP-46RZB
Remarks TEMP:22 HUMD:53 (Manual Switch)

Urms = 230.3V Freq = 49.974 Range: 2 A
Irms = 0.721A Ipik = 1.454A cf = 2.018
P = 147.4W S = 166.0VA pf = 0.888

Test - Time : 1 x 10min = 10min (100 %)

LIN (Line Impedance Network) : SLIN 0.24ohm +j0.15ohm N:0.16ohm +j0.10ohm

Limits :Plt : 0.65Pst : 1.00
dmax : 4.00 % dc : 3.30 %
dtLim: 3.30 % dt>Lim: 500ms

Test completed, Result: PASSED

Plt = 0.074

	Pst	dmax	dc	dt>Lim	Fail
		[%]	[%]	[ms]	
1	0.074	0.000	0.050	0.000	



CE EMC

TEST REPORT

For

IPC

Model: IPC-623BP00XB-ES

Trade Name: ADVANTECH

Issued for

Advantech Co., Ltd.

**No. 1, Alley 20, Lane 26, Rueiguang Road, Neihu District,
Taipei 114, Taiwan, R.O.C.**

Issued by

Compliance Certification Services Inc.

No. 81-1, Lane 210, Bade Rd., 2, Luchu Hsiang,

Taoyuan Hsien, (338) Taiwan, R.O.C.

TEL: 886-3-324-0332

FAX: 886-3-324-5235



***Note:** This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. Ltd. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document.*



TABLE OF CONTENTS

1	TEST RESULT CERTIFICATION	3
2	EUT DESCRIPTION.....	4
3	TEST METHODOLOGY.....	5
3.1	EUT SYSTEM OPERATION.....	5
3.2	DECISION OF FINAL TEST MODE.....	5
4	SETUP OF EQUIPMENT UNDER TEST.....	6
5	FACILITIES AND ACCREDITATIONS.....	7
5.1	FACILITIES.....	7
5.2	LABORATORY ACCREDITATIONS AND LISTINGS	8
6	INSTRUMENT AND CALIBRATION.....	9
6.1	MEASURING INSTRUMENT CALIBRATION.....	9
6.2	TEST AND MEASUREMENT EQUIPMENT	9
7	LINE CONDUCTED & RADIATED EMISSION TEST.....	12
7.1	LIMIT	12
7.2	TEST PROCEDURE OF LINE CONDUCTED EMISSION.....	13
7.3	TEST PROCEDURE OF COMMON MODE CONDUCTED EMISSION FOR TELECOMMUNICATION PORT	14
7.4	TEST PROCEDURE OF RADIATED EMISSION.....	15
7.5	TEST RESULTS	17
8	POWER HARMONICS TEST.....	25
9	POWER VOLTAGE FLUCTUATION / FLICKER TEST	27
10	ELECTROSTATIC DISCHARGE (ESD) IMMUNITY TEST	30
11	RADIATED ELECTROMAGNETIC FIELD IMMUNITY TEST	36
12	FAST TRANSIENTS/BURST IMMUNITY TEST.....	39
13	SURGE IMMUNITY TEST.....	41
14	CONDUCTED DISTURBANCE/INDUCED RADIO-FREQUENCY FIELD IMMUNITY TEST	43
15	POWER FREQUENCY MAGNETIC FIELD IMMUNITY TEST.....	45
16	VOLTAGE DIPS / SHORT INTERRUPTIONS	47
	APPENDIX I - PHOTOGRAPHS OF TEST SETUP	49
	APPENDIX II – TEST RESULT OF EN 61000-3-2/-3	59



1 TEST RESULT CERTIFICATION

Applicant: Advantech Co., Ltd.
No. 1, Alley 20, Lane 26, Rueiguang Road, Neihu District,
Taipei 114, Taiwan, R.O.C.

Manufacturer: Advantech Co., Ltd.
No. 1, Alley 20, Lane 26, Rueiguang Road, Neihu District,
Taipei 114, Taiwan, R.O.C.

Equipment Under Test: IPC

Trade Name: ADVANTECH

Model: IPC-623BP00XB-ES

Detailed EUT Description: See Item 2 of this report

Date of Test: January 26 ~ 28, 2005

Applicable Standard	Class/Limit/Criterion	Test Result
EN 55022: 1998	Class A	No non-compliance noted
EN 61000-3-2: 2000	Class D	No non-compliance noted
EN 61000-3-3: 1995 + A1: 2001	Limit	No non-compliance noted
EN 55024: 1998 + A1: 2001, including		
IEC 61000-4-2: 1995 + A2: 2000	Criterion B	No non-compliance noted
IEC 61000-4-3: 1995 + A2: 2000	Criterion A	No non-compliance noted
IEC 61000-4-4: 1995 + A1: 2000	Criterion B	No non-compliance noted
IEC 61000-4-5: 1995 + A1: 2000	Criterion B	No non-compliance noted
IEC 61000-4-6: 1996 + A1: 2000	Criterion A	No non-compliance noted
IEC 61000-4-8: 1993 + A1: 2000	Criterion A	No non-compliance noted
IEC 61000-4-11: 1994 + A1: 2000	Criterion B/C/C	No non-compliance noted
Deviation from Applicable Standard		
According to applicant's declaration this EUT is a class A product, and to be market in industrial environment only.		

The above equipment was tested by Compliance Certification Services Inc. for compliance with the requirements set forth in the EMC Directive 89/336/EEC and the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Approved by:

Reviewed by:

Kurt Chen
Director of Linkou Laboratory
Compliance Certification Services Inc.

Susan Su
Section Manager of Linkou Laboratory
Compliance Certification Services Inc.



2 EUT DESCRIPTION

Product	IPC		
Trade Name	ADVANTECH		
Model	IPC-623BP00XB-ES		
Housing Type	Metal Case		
EUT Power Rating	DCV From Power Supply		
Power Supply Manufacturer	Zippy	Model	HG2-6400P
			HP2-6500P
Power Supply Power Rating	For HG2-6400P I/P: 100-240VAC, 63-47Hz, 8-4A O/P: +5VDC, 35A; -5VDC, 0.5A; +12VDC, 30A; -12VDC, 0.8A; +3.3VDC, 28A; +5VSB, 2.0A For HP2-6500P I/P: 115-240VAC, 47-63Hz, 8-4A O/P: +5VDC, 40A; -5VDC, 0.8A; +12VDC, 32A; -12VDC, 1.0A; +3.3VDC, 30A; +5VSB, 2.0A		
AC Power Cord Type	Unshielded, 1.8m (Detachable)		
CPU Manufacturer	Intel	Model	P4 3.2GHz
Memory Capacity	256MB		
HDD Manufacturer	Seagate	Model	ST340014A
FDD Manufacturer	TEAC	Model	FD-235HF
CD-ROM Manufacturer	Aopan	Model	CD-9501/TKC
Chassis Manufacturer	ADVANTECH	Model	IPC-623
Backplane Manufacturer	ADVANTECH	Model	PCA-6116DP2
VGA Manufacturer	On Board		
LAN Manufacturer	On Board		

I/O Port of EUT

I/O Port Type	Q'TY	TESTED WITH
1) Serial Port	1	1
2) PS/2 Keyboard / Mouse Port	1	1
3) Video Out Port (VGA)	1	1
4) LAN Port	1	1



3 TEST METHODOLOGY

3.1 EUT SYSTEM OPERATION

1. EMI test software was loaded and executed under “Windows 2000” environment.
2. A communicated software was loaded and executed to communicate between EUT and remote side.
3. EUT sends and receives data from Notebook PC on remote side via LAN Cable.
4. Data was sent to monitor filling the screen with upper case of “H” patterns.
5. Test program sequentially exercised all related I/O’s of EUT and sent “H” patterns to all applicable output ports of EUT.
6. Repeat step 2 to 5

Note: Test program is self-repeating throughout the test.

3.2 DECISION OF FINAL TEST MODE

1. The following test mode was scanned during the preliminary test:

Mode 1

2048 × 1536 Resolution 100Mbps + HG2-6400P Power Supply

Mode 2

2048 × 1536 Resolution 10Mbps + HG2-6400P Power Supply

Mode 3

1280 × 1024 Resolution 100Mbps + HG2-6400P Power Supply

Mode 4

1024 × 768 Resolution 100Mbps + HG2-6400P Power Supply

Mode 5

640 × 480 Resolution 100Mbps + HG2-6400P Power Supply

Mode 6

2048 × 1536 Resolution 100Mbps + HP2-6500P Power Supply

Mode 7

2048 × 1536 Resolution 10Mbps + HP2-6500P Power Supply

Mode 8

1280 × 1024 Resolution 100Mbps + HP2-6500P Power Supply

Mode 9

1024 × 768 Resolution 100Mbps + HP2-6500P Power Supply

Mode 10

640 × 480 Resolution 100Mbps + HP2-6500P Power Supply

2. After the preliminary scan, the following test mode was found to produce the highest emission level.

Mode 1, 6

Then, the EUT configuration and cable configuration of the above highest emission mode was chosen for all final test items.



4 SETUP OF EQUIPMENT UNDER TEST

Setup Diagram

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

Support Equipment

No.	Equipment	Model No.	Serial No.	FCC ID	Trade Name	Data Cable	Power Cord
1	Monitor	959NF	AQ19H2RT706126P	FCC DoC	SAMSUNG	Shielded, 1.8m with two cores	Unshielded, 1.8m
2	Modem	DM-1414	304012263	IFAXDM1414	ACEEX	Unshielded, 1.5m	Unshielded, 1.8m
3	PS/2 Keyboard (One to two adapter)	Y-SP29	SYU30272823	FCC DoC	Logitech	Shielded, 1.8m	N/A
4	PS/2 Mouse (One to two adapter)	M-S34	HCA25200436	DZL211029	Logitech	Shielded, 1.8m	N/A
5	Notebook PC (Remote)	COMPAQ NC 4010	CNU441F8LV	FCC DOC	HP	LAN Cable: Unshielded, 10m	AC I/P: Unshielded, 1.8m DC O/P: Unshielded, 1.8m with a core

Note: All the above equipment/cables were placed in worse case positions to maximize emission signals during emission test.

Grounding: Grounding was in accordance with the manufacturer's requirements and conditions for the intended use.



5 FACILITIES AND ACCREDITATIONS


5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at CCS Taiwan Linkou Lab at No. 81-1, Lane 210, Bade Rd., 2, Luchu Hsiang, Taoyuan Hsien, Taiwan.

The measurement facilities are constructed in conformance with the requirements of CISPR 16-1, ANSI C63.4 and other equivalent standards.

5.2 LABORATORY ACCREDITATIONS AND LISTINGS

The test facilities used to perform Electromagnetic compatibility tests are registered or accredited by the organizations listed in the following table which includes the recognized scope specifically.

Country	Agency	Scope of Accreditation	Logo
USA	NVLAP	EN 55011, EN 55014-1, AS/NZS 1044, CNS 13783-1, EN 55022, CNS 13438, EN 61000-3-2, EN 61000-3-3, ANSI C63.4, FCC OST/MP-5, AS/NZS CISPR 22, IEC 61000-4-2, IEC 61000-4-3, IEC 61000-4-4, IEC 61000-4-5, IEC 61000-4-6, IEC 61000-4-8, IEC 61000-4-11	 Lab. Code: 200600-0
USA	FCC	3/10 meter Open Area Test Sites to perform FCC Part 15/18 measurements	 93105, 90471
Japan	VCCI	3/10 meter Open Area Test Sites and conducted test sites to perform radiated/conducted measurements	 R-393/1066/725/879/1868 C-402/747/912
Norway	NEMKO	EN 50081-1/2, EN 50082-1/2, IEC 61000-6-1/2, EN 50091-2, EN 50130-4, EN 55011, EN 55013, EN 55014-1/2, EN 55015, EN 55022, EN 55024, EN 61000-3-2/3, EN 61326-1, IEC 61000-4-2/3/4/5/6/8/11, EN 60601-1-2, EN 300 328-2, EN 300 422-2, EN 301 419-1, EN 301 489-01/03/07/08/09/17, EN 301 419-2/3, EN 300 454-2, EN 301 357-2	 ELA 124a ELA 124b ELA 124c
Taiwan	CNLA	EN 300 328-1, EN 300 328-2, EN 300 220-1, EN 300 220-2, EN 300 220-3, 47 CFR FCC Part 15 Subpart C, EN 61000-3-2, EN 61000-3-3, CNS 13439, CNS 13783-1, CNS 14115, CNS 13438, AS/NZS CISPR 22, CNS 13022-1, IEC 61000-4-2/3/4/5/6/8/11, CNS 13022-2/3	 0363 ILAC MRA
Taiwan	BSMI	CNS 13438, CNS 13783-1, CNS 13439, CNS 14115	 SL2-IS-E-0014 / IN-E-0014 /A1-E-0014 /R1-E-0014 /R2-E-0014 /L1-E-0014
Canada	Industry Canada	RSS212, Issue 1	 IC 3991-3 IC 3991-4

Note: No part of this report may be used to claim or imply product endorsement by CNLA, NVLAP or other government agency.



6 INSTRUMENT AND CALIBRATION

6.1 MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated once a year or in accordance with the manufacturer's recommendations, and is traceable under the IEC 17025 to international or national standards. Equipment has been calibrated by accredited calibration laboratories.

6.2 TEST AND MEASUREMENT EQUIPMENT

The following list contains measurement equipment used for testing. The equipment conforms to the requirement of CISPR 16-1, ANSI C63.2 and other required standards.

Calibration of all test and measurement, including any accessories that may effect such calibration, is checked frequently to ensure the accuracy. Adjustments are made and correction factors are applied in accordance with the instructions contained in the respective manual.

Equipment Used for Emission Measurement

Conducted Emission Test Site # 3				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EMI Test Receiver	R&S	ESCS30	845552/030	03/14/2005
LISN	R&S	ESH2-Z5	843285/010	01/08/2006
LISN	EMCO	3825/2	9003-1628	07/26/2005
ISN	FCC	FCC-TLISN-T4	20065	04/30/2005
ISN	FCC	FCC-TLISN-T8-02	20148	11/10/2005

Note: The measurement uncertainty is less than +/- 2.83dB, which is evaluated as per the NAMAS NIS 81 and CISPR/A/291/CDV.

Open Area Test Site # 2				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	ADVANTEST	R3261A	21720279	N.C.R
EMI Test Receiver	SCHAFFNER	SCR 3501	436	11/18/2005
Pre-Amplifier	HP	8447D	2944A08780	07/14/2005
Bilog Antenna	SCHWAZBECK	VULB9160	3065	12/11/2005
Turn Table	EMCO	2081-1.21	9709-1885	N.C.R
Antenna Tower	EMCO	2075-2	9707-2060	N.C.R
Controller	EMCO	2090	9709-1256	N.C.R
RF Switch	ANRITSU	MP59B	M76890	N.C.R
Site NSA	CCS	N/A	N/A	08/13/2005

Note: The measurement uncertainty is less than +/- 3.36dB, which is evaluated as per the NAMAS NIS 81 and CISPR/A/291/CDV.



Power Harmonic & Voltage Fluctuation/Flicker Measurement (EN 61000-3-2&-3-3)				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
HARMONICS SYSTEM	EMC-PARTNER	HARMONICS-1000	094	11/04/2005

Equipment Used for Immunity Measurement

ESD Test Site (IEC/EN 61000-4-2)				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
ESD Generator	SCHAFFNER	NSG438	170	04/19/2005

Radiated Electromagnetic Field Immunity Test Site (IEC/EN 61000-4-3)				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
S.G.	R&S	SMY02	100094	08/05/2005
Power Meter	R&S	NRVD	837794/029	08/06/2005
Power Sensor	R&S	URV5-Z2	835640/015	08/06/2005
Power Sensor	R&S	URV5-Z2	835640/016	08/06/2005
Power Amplifier	ar	150W1000	300300	N.C.R

Fast Transients/Burst Test Site (IEC/EN 61000-4-4)				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Fast Transients/Burst Generator	HAEFELY TRENCH	PEFT- JUNIOR	583 333-117	08/25/2005
Clamp	HAEFELY TRENCH	093 506.1	080 421.13	N.C.R

Surge Immunity Test Site (IEC/EN 61000-4-5)				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Surge Tester	HAEFELY TRENCH	PSUGER 4010	583 334-71	08/25/2005



CS Test Site (IEC/EN 61000-4-6)				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
S.G.	R&S	SMY02	100094	08/05/2005
Power Meter	R&S	NRVD	837794/029	08/06/2005
Power Sensor	R&S	URV5-Z2	835640/015	08/06/2005
Power Sensor	R&S	URV5-Z2	835640/016	08/06/2005
Power Amplifier	ar	500A100A	300299	N.C.R
CDN	Lüthi	801-M3	1879	03/03/2005
CDN	FRANKONIA	CDN-M2	A3002010	08/06/2005
CDN	SCHAFFNER	T400	16906	12/29/2005

Power Frequency Magnetic Field Immunity Test Site (IEC/EN 61000-4-8)				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
TRIAX ELF Magnetic Field Meter	F.W.BELL	4090	9711	11/21/2005
Magnetic Field Tester	HAEFELY TRENCH	MAG 100.1	080 938-01	N.C.R

Voltage Dips/Short Interruption and Voltage Variation Immunity Test Site (IEC/EN 61000-4-11)				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Dips/Interruption and Variations Simulator	HAEFELY TRENCH	PLINE 1610	080 344-05	04/06/2005



7 LINE CONDUCTED & RADIATED EMISSION TEST

7.1 LIMIT

Maximum permissible level of Line Conducted Emission

Frequency (MHZ)	Class A (dBuV)		Class B (dBuV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 - 0.5	79	66	66 - 56	56 - 46
0.50 - 5.0	73	60	56	46
5.0 - 30.0	73	60	60	50

Note: The lower limit shall apply at the transition frequency.

Maximum permissible level of Common Mode Conducted Emission (Telecommunication Ports)

CLASS A

Frequency (MHZ)	Voltage Limit (dBuV)		Current Limit (dBuA)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 - 0.5	97 – 87	84 - 74	53 – 43	40 – 30
0.5 - 30.0	87	74	43	30

Note: The lower limit shall apply at the transition frequency.

CLASS B

Frequency (MHZ)	Voltage Limit (dBuV)		Current Limit (dBuA)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 - 0.5	84 - 74	74 - 64	40 – 30	30 – 20
0.5 - 30.0	74	64	30	20

Note: The lower limit shall apply at the transition frequency.

Maximum permissible level of Radiated Emission measured at 10 meter

Frequency (MHZ)	Class A (dBuV/m)	Class B (dBuV/m)
	Quasi-peak	Quasi-peak
30 – 230	40	30
230 - 1000	47	37

Note: The lower limit shall apply at the transition frequency.



7.2 TEST PROCEDURE OF LINE CONDUCTED EMISSION

Procedure of Preliminary Test

- The EUT was set up as per the test configuration to simulate typical usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per EN 55022 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- Support equipment, if needed, was placed as per EN 55022.
- All I/O cables were positioned to simulate typical actual usage as per EN 55022.
- The test equipment EUT installed received AC power, 230VAC/50Hz, through a Line Impedance Stabilization Network (LISN), which supplied power source and was grounded to the ground plane.
- All support equipment received power from a second LISN.
- The EUT test program was started. Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.
- The Receiver scanned from 150kHz to 30MHz for emissions in each of the test modes.
- During the above scans, the emissions were maximized by cable manipulation.
- The test mode(s) described in Item 3.2 were scanned during the preliminary test.
- After the preliminary scan, we found the test mode described in Item 3.2 producing the highest emission level.
- The EUT configuration and cable configuration of the above highest emission level were recorded for reference of the final test.

Procedure of Final Test

- EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.
- A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less -2dB to the Average limit in Q.P. mode, then the emission signal was re-checked using an Average detector.
- The test data of the worst-case condition(s) was recorded.

**Data Sample:**

Freq. (MHz)	Q.P. Raw (dBuV)	Average Raw (dBuV)	Q.P. Limit (dBuV)	Average Limit (dBuV)	Q.P. Margin (dB)	Average Margin (dB)	Note
x.xx	43.95	---	73.00	60.00	-29.05	---	L1

Freq. = Emission frequency in MHz

Raw dBuV = Uncorrected Analyzer/Receiver reading + Insertion loss of LISN, if it > 0.5 dB

Limit dBuV = Limit stated in standard

Margin dB = Reading in reference to limit

Note = Current carrying line of reading

“---“ = The emission level complied with the Average limits, with at least 2dB margin limits, so no further recheck.

Calculation Formula

Margin (dB) = RAW (dBuV) – Limit (dBuV)

7.3 TEST PROCEDURE OF COMMON MODE CONDUCTED EMISSION FOR TELECOMMUNICATION PORT

- Selecting ISN for unscreened cable or a current probe for screened cable to take measurement.
- The port of the EUT was connected to the remote side support equipment through the ISN/Current Probe and communication in normal condition.
- Making a overall range scan by using the test receiver controlled by controller and record at least six highest emissions for showing in the test report.
- Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.
- In case of measuring on the screened cable, the current limit shall be applied, otherwise the voltage limit should be applied.
- The following test mode(s) were scanned during the preliminary test:

Mode 1

10/100 Mbps (HG2-6400P Power Supply)

Mode 2

10/100 Mbps (HP2-6500P Power Supply)

- After the preliminary scan, we found the following test mode(s) producing the highest emission level and test data of the worst case was recorded.

Mode 1, 2

**Data Sample:**

Freq. (MHz)	Q.P. Raw (dBuV)	AV. Raw (dBuV)	Q.P. Limit (dBuV)	AV. Limit (dBuV)	Q.P. Margin (dB)	AV. Margin (dB)	Note
x.xx	43.95	---	87.00	74.00	-43.05	---	---

Freq.: Emission frequency

Raw: Uncorrected Analyzer / Receiver reading

Limit: Limit stated in standard

Margin: Reading in reference to limit

Note: Current carrying line of reading

“--”: The emission level complied with the Average limits, with at least 2 dB margin, so no further recheck.

7.4 TEST PROCEDURE OF RADIATED EMISSION

Procedure of Preliminary Test

- The equipment was set up as per the test configuration to simulate typical usage per the user's manual. When the EUT is a tabletop system, a wooden turntable with a height of 0.8 meters is used which is placed on the ground plane. When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- Support equipment, if needed, was placed as per EN 55022.
- All I/O cables were positioned to simulate typical usage as per EN 55022.
- The EUT received AC power source, 230VAC/50Hz, from the outlet socket under the turntable. All support equipment received power from another socket under the turntable.
- The antenna was placed at 10 meter away from the EUT as stated in EN 55022. The antenna connected to the Spectrum Analyzer via a cable and at times a pre-amplifier would be used.
- The Analyzer / Receiver quickly scanned from 30MHz to 1000MHz. The EUT test program was started. Emissions were scanned and measured rotating the EUT to 360 degrees and positioning the antenna 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level.
- The test mode(s) described in Item 3.2 were scanned during the preliminary test:
- After the preliminary scan, we found the test mode described in Item 3.2 producing the highest emission level.
- The EUT and cable configuration, antenna position, polarization and turntable position of the above highest emission level were recorded for the final test.

**Procedure of Final Test**

- EUT and support equipment were set up on the turntable as per the configuration with highest emission level in the preliminary test.
- The Analyzer / Receiver scanned from 30MHz to 1000MHz. Emissions were scanned and measured rotating the EUT to 360 degrees, varying cable placement and positioning the antenna 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level.
- Recorded at least the six highest emissions. Emission frequency, amplitude, antenna position, polarization and turntable position were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit and only Q.P. reading is presented.
- The test data of the worst-case condition(s) was recorded.

Data Sample:

Freq. (MHz)	Raw Data (dBuV)	Corr. Factor (dB/m)	Emiss. Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)
xx.xx	14.00	12.20	26.20	40.00	-13.80

Freq.	= Emission frequency in MHz
Raw Data (dBuV)	= Uncorrected Analyzer / Receiver reading
Corr. Factor (dB/m)	= Antenna factor + Cable loss – Amplifier gain
Emiss. Level (dBuV/m)	= Raw reading converted to dBuV/m and CF added
Limit (dBuV/m)	= Limit stated in standard
Margin (dB)	= Reading in reference to limit
P	= Peak Reading
Q	= Quasi-peak Reading
A	= Average Reading

Calculation Formula

Margin (dB) = Emiss. Level (dBuV/m) – Limits (dBuV/m)

Emission Level (dBuV/m) = Raw Data (dBuV) + Corr. Factor (dB/m)



7.5 TEST RESULTS

Line Conducted Emission

Model: IPC-623BP00XB-ES**Test Mode:** Mode 1**Temperature:** 23°C**Humidity:** 56% RH**Tested by:** Ken Jung**Test Results:** Pass

(The chart below shows the highest readings taken from the final data)

Freq. (MHz)	Q.P. Raw (dBuV)	AVG Raw (dBuV)	Q.P. Limit (dBuV)	AVG Limit (dBuV)	Q.P. Margin (dB)	AVG Margin (dB)	NOTE
0.271	37.40	---	79.00	66.00	-41.60	---	L1
1.265	31.70	---	73.00	60.00	-41.30	---	L1
3.277	31.00	---	73.00	60.00	-42.00	---	L1
7.284	30.90	---	73.00	60.00	-42.10	---	L1
21.665	32.40	---	73.00	60.00	-40.60	---	L1
23.134	30.50	---	73.00	60.00	-42.50	---	L1
0.270	37.10	---	79.00	66.00	-41.90	---	L2
0.991	31.90	---	73.00	60.00	-41.10	---	L2
6.945	31.80	---	73.00	60.00	-41.20	---	L2
7.346	35.40	---	73.00	60.00	-37.60	---	L2
21.665	32.30	---	73.00	60.00	-40.70	---	L2
23.137	30.40	---	73.00	60.00	-42.60	---	L2

L1 = Line One (Live Line) / L2 = Line Two (Neutral Line)

Note: “---” denotes the emission level was or more than 2dB below the Average limit, so no re-check anymore.

**Line Conducted Emission****Model:** IPC-623BP00XB-ES**Test Mode:** Mode 6**Temperature:** 23°C**Humidity:** 56% RH**Tested by:** Ken Jung**Test Results:** Pass

(The chart below shows the highest readings taken from the final data)

Freq. (MHz)	Q.P. Raw (dBuV)	AVG Raw (dBuV)	Q.P. Limit (dBuV)	AVG Limit (dBuV)	Q.P. Margin (dB)	AVG Margin (dB)	NOTE
0.155	63.10	---	79.00	66.00	-15.90	---	L1
6.255	45.50	---	73.00	60.00	-27.50	---	L1
10.014	38.10	---	73.00	60.00	-34.90	---	L1
11.856	39.40	---	73.00	60.00	-33.60	---	L1
13.867	36.50	---	73.00	60.00	-36.50	---	L1
28.289	37.10	---	73.00	60.00	-35.90	---	L1
0.155	63.30	---	79.00	66.00	-15.70	---	L2
6.314	40.10	---	73.00	60.00	-32.90	---	L2
8.756	45.40	---	73.00	60.00	-27.60	---	L2
10.163	39.90	---	73.00	60.00	-33.10	---	L2
12.504	49.30	---	73.00	60.00	-23.70	---	L2
29.946	41.10	---	73.00	60.00	-31.90	---	L2

L1 = Line One (Live Line) / L2 = Line Two (Neutral Line)

Note: “---” denotes the emission level was or more than 2dB below the Average limit, so no re-check anymore.

**Common Mode Conducted Emission****Model:** IPC-623BP00XB-ES**Test Mode:** Mode 1**Temperature:** 23°C**Humidity:** 56% RH**Tested by:** Ken Jung**Test Results:** Pass

(The chart below shows the highest readings taken from the final data)

Freq. (MHz)	Q.P. Raw (dBuV)	AVG Raw (dBuV)	Q.P. Limit (dBuV)	AVG Limit (dBuV)	Q.P. Margin (dB)	AVG Margin (dB)	NOTE
4.896	57.30	---	87.00	74.00	-29.70	---	10Base
6.134	56.90	---	87.00	74.00	-30.10	---	10Base
7.517	64.90	---	87.00	74.00	-22.10	---	10Base
8.756	69.30	---	87.00	74.00	-17.70	---	10Base
10.663	61.20	---	87.00	74.00	-25.80	---	10Base
12.519	67.40	---	87.00	74.00	-19.60	---	10Base
13.421	65.10	---	87.00	74.00	-21.90	---	100Base
16.174	64.40	---	87.00	74.00	-22.60	---	100Base
16.233	65.60	---	87.00	74.00	-21.40	---	100Base
18.247	63.90	---	87.00	74.00	-23.10	---	100Base
19.716	65.30	---	87.00	74.00	-21.70	---	100Base
23.134	67.20	---	87.00	74.00	-19.80	---	100Base

L1 = Line One (Live Line) / L2 = Line Two (Neutral Line)

Note: “---” denotes the emission level was or more than 2dB below the Average limit, so no re-check anymore.

**Common Mode Conducted Emission****Model:** IPC-623BP00XB-ES**Test Mode:** Mode 2**Temperature:** 23°C**Humidity:** 56% RH**Tested by:** Ken Jung**Test Results:** Pass

(The chart below shows the highest readings taken from the final data)

Freq. (MHz)	Q.P. Raw (dBuV)	AVG Raw (dBuV)	Q.P. Limit (dBuV)	AVG Limit (dBuV)	Q.P. Margin (dB)	AVG Margin (dB)	NOTE
4.956	63.10	---	87.00	74.00	-23.90	---	10Base
6.144	60.50	---	87.00	74.00	-26.50	---	10Base
10.014	67.90	---	87.00	74.00	-19.10	---	10Base
11.196	62.30	---	87.00	74.00	-24.70	---	10Base
11.905	63.10	---	87.00	74.00	-23.90	---	10Base
13.753	62.90	---	87.00	74.00	-24.10	---	10Base
13.426	64.70	---	87.00	74.00	-22.30	---	100Base
16.175	63.40	---	87.00	74.00	-23.60	---	100Base
16.237	64.50	---	87.00	74.00	-22.50	---	100Base
18.244	63.90	---	87.00	74.00	-23.10	---	100Base
19.716	64.50	---	87.00	74.00	-22.50	---	100Base
23.139	66.90	---	87.00	74.00	-20.10	---	100Base

L1 = Line One (Live Line) / L2 = Line Two (Neutral Line)

Note: “---” denotes the emission level was or more than 2dB below the Average limit, so no re-check anymore.

**Radiated Emission (A)****Model:** IPC-623BP00XB-ES**Test Mode:** Mode 1**Temperature:** 23°C**Humidity:** 57% RH**Detector Function:** Quasi-peak.**Antenna:** Vertical at 10m**Tested by:** Ken Jung**Test Results:** Pass

(The chart below shows the highest readings taken from the final data)

Freq. (MHz)	Raw Data (dBuV)	Corr. Factor (dB/m)	Emiss. Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)
44.51	19.1	12.3	31.4	40.0	-8.6
55.27	24.7	9.4	34.1	40.0	-5.9
69.10	27.2	10.1	37.3	40.0	-2.7
72.74	21.8	10.2	32.0	40.0	-8.0
133.33	21.1	15.7	36.8	40.0	-3.2
165.99	22.2	14.3	36.5	40.0	-3.5
186.51	23.7	14.2	37.9	40.0	-2.1
200.01	22.6	14.7	37.3	40.0	-2.7
213.17	21.9	14.2	36.1	40.0	-3.9
250.11	26.7	14.6	41.3	47.0	-5.7
300.11	18.8	16.0	34.8	47.0	-12.2
320.40	23.2	16.9	40.1	47.0	-6.9
360.30	18.4	18.3	36.7	47.0	-10.3
450.93	16.4	20.3	36.7	47.0	-10.3
586.40	15.2	23.2	38.4	47.0	-8.6
613.60	16.8	23.6	40.4	47.0	-6.6
746.70	12.5	25.1	37.6	47.0	-9.4

**Radiated Emission (B)****Model:** IPC-623BP00XB-ES**Test Mode:** Mode 1**Temperature:** 23°C**Humidity:** 57% RH**Detector Function:** Quasi-peak.**Antenna:** Horizontal at 10m**Tested by:** Ken Jung**Test Results:** Pass

(The chart below shows the highest readings taken from the final data)

Freq. (MHz)	Raw Data (dBuV)	Corr. Factor (dB/m)	Emiss. Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)
65.41	21.2	9.8	31.0	40.0	-9.0
69.14	22.3	10.1	32.4	40.0	-7.6
132.70	16.3	15.7	32.0	40.0	-8.0
150.13	17.7	14.9	32.6	40.0	-7.4
159.97	16.9	14.4	31.3	40.0	-8.7
166.14	18.2	14.2	32.4	40.0	-7.6
186.77	22.2	14.2	36.4	40.0	-3.6
200.01	20.9	14.7	35.6	40.0	-4.4
213.15	20.1	14.2	34.3	40.0	-5.7
236.66	24.8	14.1	38.9	47.0	-8.1
300.12	21.6	16.0	37.6	47.0	-9.4
346.90	19.9	18.1	38.0	47.0	-9.0
453.00	20.2	20.4	40.6	47.0	-6.4
586.33	18.4	23.2	41.6	47.0	-5.4
613.60	18.4	23.6	42.0	47.0	-5.0
704.60	14.8	25.0	39.8	47.0	-7.2
878.90	8.7	27.4	36.1	47.0	-10.9

**Radiated Emission (A)****Model:** IPC-623BP00XB-ES**Test Mode:** Mode 6**Temperature:** 20°C**Humidity:** 64% RH**Detector Function:** Quasi-peak.**Antenna:** Vertical at 10m**Tested by:** Ken Jung**Test Results:** Pass

(The chart below shows the highest readings taken from the final data)

Freq. (MHz)	Raw Data (dBuV)	Corr. Factor (dB/m)	Emiss. Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)
53.90	20.0	9.4	29.4	40.0	-10.6
133.47	20.7	15.7	36.4	40.0	-3.6
166.89	21.7	14.2	35.9	40.0	-4.1
186.69	23.8	14.2	38.0	40.0	-2.0
200.89	18.7	14.7	33.4	40.0	-6.6
213.89	20.9	14.1	35.0	40.0	-5.0
300.70	19.1	16.0	35.1	47.0	-11.9
451.58	19.8	20.3	40.1	47.0	-6.9
614.89	18.7	23.6	42.3	47.0	-4.7
746.84	14.1	25.1	39.2	47.0	-7.8

**Radiated Emission (B)****Model:** IPC-623BP00XB-ES**Test Mode:** Mode 6**Temperature:** 20°C**Humidity:** 64% RH**Detector Function:** Quasi-peak.**Antenna:** Horizontal at 10m**Tested by:** Ken Jung**Test Results:** Pass

(The chart below shows the highest readings taken from the final data)

Freq. (MHz)	Raw Data (dBuV)	Corr. Factor (dB/m)	Emiss. Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)
69.89	20.1	10.2	30.3	40.0	-9.7
133.58	17.0	15.7	32.7	40.0	-7.3
186.47	19.4	14.2	33.6	40.0	-6.4
200.70	17.1	14.7	31.8	40.0	-8.2
213.98	20.1	14.1	34.2	40.0	-5.8
249.80	17.5	14.6	32.1	47.0	-14.9
300.56	21.6	16.0	37.6	47.0	-9.4
454.98	17.4	20.4	37.8	47.0	-9.2
587.00	17.4	23.2	40.6	47.0	-6.4
614.70	19.1	23.6	42.7	47.0	-4.3
745.28	15.4	25.1	40.5	47.0	-6.5




8 POWER HARMONICS TEST

Port : AC mains
Basic Standard : EN 61000-3-2 (2000)
Limits : ☐ CLASS A ; ☐ CLASS B ; ☐ CLASS C ; ☒ CLASS D
Tested by : Ken Jung
Temperature : 20 / 26°C
Humidity : 59 / 51% RH
Test Mode : 1, 6

Limit:

Limits for Class A equipment		Limits for Class D equipment		
Harmonics Order n	Max. permissible harmonics current A	Harmonics Order n	Max. permissible harmonics current per watt mA/W	Max. permissible harmonics current A
Odd harmonics		Odd Harmonics only		
3	2.30	3	3.4	2.30
5	1.14	5	1.9	1.14
7	0.77	7	1.0	0.77
9	0.40	9	0.5	0.40
11	0.33	11	0.35	0.33
13	0.21	13	0.30	0.21
15<=n<=39	0.15x15/n	15<=n<=39	3.85/n	0.15x15/n
Even harmonics				
2	1.08			
4	0.43			
6	0.30			
8<=n<=40	0.23x8/n			

Block Diagram of Test Setup:**Test Procedure:**

- a. The EUT was placed on the top of a wooden table 0.8 meters above the ground and operated to produce the maximum harmonic components under normal operating conditions for each successive harmonic component in turn.
- b. The correspondent test program of test instrument to measure the current harmonics emanated from EUT is chosen. The measure time shall be not less than the time necessary for the EUT to be exercised.

Test Result : (See Appendix II for details)**PASS****FAIL**


9 POWER VOLTAGE FLUCTUATION / FLICKER TEST

Port : AC mains
Basic Standard : EN 61000-3-3 (1995 + A1: 2001)
Limits : §5 of EN 61000-3-3
Tested by : Ken Jung
Temperature : 26°C
Humidity : 55% RH
Test Mode : 1, 6

Limit:

TEST ITEM	LIMIT	REMARK
P_{st}	1.0	P_{st} means short-term flicker indicator.
P_{lt}	0.65	P_{lt} means long-term flicker indicator.
T_{dt} (ms)	500	T_{dt} means maximum time that dt exceeds 3 %.
d_{max} (%)	4%	d_{max} means maximum relative voltage change.
dc (%)	3.3%	dc means relative steady-state voltage change

Block Diagram of Test Setup:



Test Procedure:

- a. The EUT was placed on the top of a wooden table 0.8 meters above the ground and operated to produce the most unfavorable sequence of voltage changes under normal operating conditions.
- b. During the flick measurement, the measure time shall include that part of whole operation cycle in which the EUT produce the most unfavorable sequence of voltage changes. The observation period for short-term flicker indicator is 10 minutes and the observation period for long-term flicker indicator is 2 hours.

Test Result: (See Appendix II for details)**Mode 1****Continue**

Test Parameter	Measurement Value	Limit	Result
P _{st}	0.072	1.0	Pass
P _{lt}	0.072	0.65	Pass
T _{dt} (ms)	0	500	Pass
d _{max} (%)	0%	4%	Pass
dc (%)	0.01%	3.3%	Pass

Manual Switch

Test Parameter	Measurement Value	Limit	Result
P _{st}	0.083	1.0	Pass
P _{lt}	0.083	0.65	Pass
T _{dt} (ms)	0	500	Pass
d _{max} (%)	0.21%	4%	Pass
dc (%)	0.1%	3.3%	Pass

**Mode 6
Continue**

Test Parameter	Measurement Value	Limit	Result
P _{st}	0.072	1.0	Pass
P _{lt}	0.072	0.65	Pass
T _{dt} (ms)	0	500	Pass
d _{max} (%)	0%	4%	Pass
dc (%)	0.01%	3.3%	Pass

Manual Switch


Test Parameter	Measurement Value	Limit	Result
P _{st}	0.078	1.0	Pass
P _{lt}	0.078	0.65	Pass
T _{dt} (ms)	0	500	Pass
d _{max} (%)	0%	4%	Pass
dc (%)	0.07%	3.3%	Pass

10 ELECTROSTATIC DISCHARGE (ESD) IMMUNITY TEST

Port	: Enclosure
Basic Standard	: IEC/EN 61000-4-2
Test Level	: ± 8 kV (Air Discharge) ± 4 kV (Contact Discharge) ± 4 kV (Indirect Discharge)
Performance Criterion	: B (Standard Required)
Tested by	: Ken Jung
Temperature	: 23°C
Humidity	: 55 / 54% RH
Pressure	: 1015mbar
Test Mode	: 1, 6

Block Diagram of Test Setup:

(The 470 k ohm resistors are installed per standard requirement.)



**Test Procedure:**

1. The EUT was located 0.1 m minimum from all side of the HCP.
2. The indirect support units were located 1 m minimum away from the EUT, but direct support unit was/were located at same location as EUT on the HCP and keep at a distance of 10 cm with EUT.
3. A scroll 'H' test program was loaded and executed in Windows 2000 mode.
4. The EUT sent above message to monitor and related peripherals through the test.
5. Active the communication function if the EUT with such port(s).
6. As per the requirement of EN 55024; applying direct contact discharge at the sides other than front of EUT at minimum 50 discharges (25 positive and 25 negative) if applicable, can't be applied direct contact discharge side of EUT then the indirect discharge shall be applied. One of the test points shall be subjected to at least 50 indirect discharge (contact) to the front edge of horizontal coupling plane.
7. Other parts of EUT where it is not possible to perform contact discharge then selecting appropriate points of EUT for air discharge, a minimum of 10 single air discharges shall be applied.
8. The application of ESD to the contact of open connectors is not required.
9. The EUT direct connection units also need to be applied ESD at the port of EUT cable connected.
10. Putting a mark on EUT to show tested points. The following test condition was followed during the tests.

Note: As per IEC/EN 61000-4-2, two 470k bleed resistors cable is connected between the EUT and HCP during the test applicable for power ungrounded or battery operating unit only.

The electrostatic discharges were applied as follows:

Amount of discharge	Voltage	Coupling	Result (Pass/Fail)
Mini 10 /Point	± 8 kV	Air Discharge	Pass
Mini 25 /Point	± 4 kV	Contact Discharge	Pass
Mini 25 /Point	± 4 kV	Indirect Discharge HCP	Pass
Mini 25 /Point	± 4 kV	Indirect Discharge VCP (Right)	Pass
Mini 25 /Point	± 4 kV	Indirect Discharge VCP (Left)	Pass

For the tested points to EUT, please refer to attached page.

(Blue arrow mark for Contact Discharge and red arrow mark for Air Discharge)



Performance & Result:

- ☒ **Criteria A:** The apparatus continues to operate as intended. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance.
- ☐ **Criteria B:** The apparatus continues to operate as intended after the test. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance. During the test, degradation of performance is however allowed.
- ☐ **Criteria C:** Temporary loss of function is allowed, provided the functions self recoverable or can be restored by the operation of controls.

☒ **PASS** ☐ **FAIL**

Observation: No function degraded during the tests.

The Tested Points of EUT

Photo 1 of 5



Photo 2 of 5





Photo 3 of 5



Photo 4 of 5






Photo 5 of 5



11 RADIATED ELECTROMAGNETIC FIELD IMMUNITY TEST

Port	: Enclosure
Basic Standard	: IEC/EN 61000-4-3
Requirements	: 10V/m / with 80% AM. 1kHz Modulation. (Customer Required)
Performance Criterion	: A (Standard Required)
Tested by	: Ken Jung
Temperature	: 21°C
Humidity	: 57% RH
Pressure	: 1015mbar
Test Mode	: 1, 6

Block Diagram of Test Setup:



Test Procedure:

1. The EUT was located at the edge of supporting table keep 3 meter away from transmitting antenna, it just the calibrated square area of field uniformity. The support units were located outside of the uniformity area, but the cable(s) connected with EUT were exposed to the calibrated field as per IEC/EN 61000-4-3.
2. Setting the testing parameters of RS test software per IEC/EN 61000-4-3.
3. Performing the pre-test at each side of with double specified level (6V/m) at 4% steps.
4. From the result of pre-test in step 5, choice the worst side of EUT for final test from 80 MHz to 1000 MHz at 1% steps.
5. Recording the test result in following table.
6. It is not necessary to perform test as per annex A of EN 55024 if the EUT doesn't belong to ITE product.

Preliminary test conditions:

Test level : 10V/m
Steps : 4 % of fundamental
Dwell Time : 3 sec

Range (MHz)	Field	Modulation	Polarity	Position	Result (Pass/Fail)
80-1000	10V/m	Yes	H	Front	Pass
80-1000	10V/m	Yes	V	Front	Pass
80-1000	10V/m	Yes	H	Right	Pass
80-1000	10V/m	Yes	V	Right	Pass
80-1000	10V/m	Yes	H	Back	Pass
80-1000	10V/m	Yes	V	Back	Pass
80-1000	10V/m	Yes	H	Left	Pass
80-1000	10V/m	Yes	V	Left	Pass

Final test conditions:

Test level : 10V/m
Steps : 1 % of fundamental
Dwell Time : 3 sec

Range (MHz)	Field	Modulation	Polarity	Position	Result (Pass/Fail)
80-1000	10V/m	Yes	H	Back	Pass
80-1000	10V/m	Yes	V	Back	Pass



Performance & Result:

- ☒ **Criteria A:** The apparatus continues to operate as intended. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance.
- ☐ **Criteria B:** The apparatus continues to operate as intended after the test. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance. During the test, degradation of performance is however allowed.
- ☐ **Criteria C:** Temporary loss of function is allowed, provided the functions self recoverable or can be restored by the operation of controls.


☒ **PASS** ☐ **FAIL**

Observation: No function degraded during the tests.

12 FAST TRANSIENTS/BURST IMMUNITY TEST

Port	: On Power Supply Line and LAN Cable
Basic Standard	: IEC/EN 61000-4-4
Requirements	: ± 2 kV for Power Supply Line (Customer Required) ± 1 kV for LAN Cable (Customer Required)
Performance Criteria	: B (Standard Required)
Tested by	: Ken Jung
Temperature	: 22 / 21°C
Humidity	: 54% RH
Pressure	: 1015mbar
Test Mode	: 1, 6

Block Diagram of Test Setup:



Test Procedure:

1. The EUT and support units were located on a wooden table 0.8 m away from ground reference plane.
2. A 1.0 meter long power cord was attached to EUT during the test.
3. The length of communication cable between communication port and clamp was keeping within 1 meter.
4. Injected test voltage to the EUT ports from minimum to standard request or client request.
5. Recording the test result as shown in following table.

**Test conditions:**

Impulse Frequency : 5kHz
Tr/Th : 5/50ns
Burst Duration : 15ms
Burst Period : 3Hz

Inject Line	Voltage kV	Inject Method	Result (Pass/Fail)
L	± 2	Direct	Pass
N	± 2	Direct	Pass
PE	± 2	Direct	Pass
L + N	± 2	Direct	Pass
L + PE	± 2	Direct	Pass
N + PE	± 2	Direct	Pass
L + N + PE	± 2	Direct	Pass
RJ 45 Port (LAN Cable)	± 1	Clamp	Pass

Performance & Result:

- ☐ **Criteria A:** The apparatus continues to operate as intended. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance.
- ☒ **Criteria B:** The apparatus continues to operate as intended after the test. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance. During the test, degradation of performance is however allowed.
- ☐ **Criteria C:** Temporary loss of function is allowed, provided the functions self recoverable or can be restored by the operation of controls.

☒ **PASS** ☐ **FAIL**

Observation: The LAN Port was lost communicated, but can be auto recovered as the events disappear.

13 SURGE IMMUNITY TEST

Port : Power Cord and LAN Cable

Basic Standard : IEC/EN 61000-4-5

Requirements : ± 1 kV (Line to Line)
 ± 2 kV (Line to Ground)

Performance Criteria : B (Standard Required)

Tested by : Ken Jung


Temperature : 23°C

Humidity : 54 / 53% RH

Pressure : 1015mbar

Test Mode : 1, 6

Block Diagram of Test Setup:



Test Procedure:

1. The EUT and support units were located on a wooden table 0.8 m away from ground floor.
2. Injected test voltage to the EUT ports from minimum to standard request or client request.
3. Recording the test result as shown in following table.

**Test conditions:**

Voltage Waveform : 1.2/50 μ s
Current Waveform : 8/20 μ s
Polarity : Positive/Negative
Phase angle : 0°, 90°, 270°
Number of Test : 5

Coupling Line	Voltage (kV)	Polarity	Coupling Method	Result (Pass/Fail)
L1-L2	1	Positive	Capacitive	Pass
L1-PE	2	Positive	Capacitive	Pass
L2-PE	2	Positive	Capacitive	Pass
L1-L2	1	Negative	Capacitive	Pass
L1-PE	2	Negative	Capacitive	Pass
L2-PE	2	Negative	Capacitive	Pass

Performance & Result:

- ☒ **Criteria A:** The apparatus continues to operate as intended. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance.
- ☐ **Criteria B:** The apparatus continues to operate as intended after the test. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance. During the test, degradation of performance is however allowed.
- ☐ **Criteria C:** Temporary loss of function is allowed, provided the functions self recoverable or can be restored by the operation of controls.

☒ **PASS** ☐ **FAIL**


Observation: No function degraded during the tests.

14 CONDUCTED DISTURBANCE/INDUCED RADIO-FREQUENCY FIELD IMMUNITY TEST


Port	: AC Port and LAN Cable
Basic Standard	: IEC/EN 61000-4-6
Requirements	: 10V with 80% AM. 1kHz Modulation. (Customer Required)
Injection Method	: CDN-M3 for Power Cord CDN-T4 for LAN Cable
Performance Criterion	: A (Standard Required)
Tested by	: Ken Jung
Temperature	: 22°C
Humidity	: 56 / 57% RH
Pressure	: 1015mbar
Test Mode	: 1, 6

Block Diagram of Test Setup:

Side View:



Top View:



**Test Procedure:**

1. The EUT and support units were located at a ground reference plane with the interposition of a 0.1 m thickness insulating support and the CDN was located on GRP directly.
2. Setting the testing parameters of CS test software as per IEC/EN 61000-4-6.
3. Recording the test result in following table.

Test conditions:

Frequency Range : 0.15MHz-80MHz

Frequency Step : 1% of fundamental

Dwell Time : 3 sec

Range (MHz)	Field	Modulation	Result (Pass/Fail)
0.15-80	10V	Yes	Pass

Performance & Result:


- ☒ **Criteria A:** The apparatus continues to operate as intended. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance.
- ☐ **Criteria B:** The apparatus continues to operate as intended after the test. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance. During the test, degradation of performance is however allowed.
- ☐ **Criteria C:** Temporary loss of function is allowed, provided the functions self recoverable or can be restored by the operation of controls.

☒ **PASS** ☐ **FAIL****Observation:** No function degraded during the tests.

15 POWER FREQUENCY MAGNETIC FIELD IMMUNITY TEST

Port : Enclosure
Basic Standard : IEC/EN 61000-4-8
Requirements : 30 A/m (Customer Required)
Performance Criterion : A (Standard Required)
Tested by : Ken Jung
Temperature : 24°C
Humidity : 57% RH
Pressure : 1015mbar
Test Mode : 1, 6

Block Diagram of Test Setup:



Test Procedure:

1. The EUT and support units were located on Ground Reference Plane with the interposition of a 0.1 m thickness insulation support.
2. Putting the induction coil on horizontal direction. (X direction)
3. Rotating the induction coil by 90° (Y direction)
4. Rotating the induction coil by 90° again (Z direction)
5. Recording the test result as shown in following table.

**Test conditions:**

Field Strength: 30A/m

Power Freq.: 50Hz

Orientation: X, Y, Z

Orientation	Field	Result (Pass/Fail)	Remark
X	30A/m	Pass	
Y	30A/m	Pass	
Z	30A/m	Pass	

Performance & Result:

- ☒ **Criteria A:** The apparatus continues to operate as intended. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance.
- ☐ **Criteria B:** The apparatus continues to operate as intended after the test. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance. During the test, degradation of performance is however allowed.
- ☐ **Criteria C:** Temporary loss of function is allowed, provided the functions self recoverable or can be restored by the operation of controls.

☒ **PASS** ☐ **FAIL****Observation:** No function degraded during the tests.

16 VOLTAGE DIPS / SHORT INTERRUPTIONS

Port : AC mains

Basic Standard : IEC/EN 61000-4-11

Requirement : PHASE ANGLE 0, 45, 90, 135, 180, 225, 270, 315 degrees

Voltage Dips	Test Level % U_T	Reduction (%)	Duration (periods)	Performance Criteria
	<5	>95	0.5	B
	70	30	25	C

Voltage Interceptions	Test Level % U_T	Reduction (%)	Duration (periods)	Performance Criteria
	<5	>95	250	C

Test Interval : Min. 10 sec.

Tested by : Ken Jung


Temperature : 23°C

Humidity : 56 / 54% RH

Pressure : 1015mbar

Test Mode : 1, 6

Block Diagram of Test Setup:



Test Procedure:

1. The EUT and support units were located on a wooden table, 0.8 m away from ground floor.
2. Setting the parameter of tests and then Perform the test software of test simulator.
3. Conditions changes to occur at 0 degree crossover point of the voltage waveform.
4. Recording the test result in test record form.

**Test conditions**

The duration with a sequence of three dips/interruptions with interval of 10 s minimum
(Between each test event)

Voltage Dips:

Test Level % U _T	Reduction (%)	Duration (periods)	Observation	Meet Performance Criteria
0	100	0.5	Normal	A
70	30	25	Normal	A

Voltage Interruptions:

Test Level % U _T	Reduction (%)	Duration (periods)	Observation	Meet Performance Criteria
0	100	250	EUT shut down but can be recovered by manual, as the events disappear.	C

Normal: No any functions degrade during and after the test.

Performance & Result:

Criteria A: The apparatus continues to operate as intended. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance.

Criteria B: The apparatus continues to operate as intended after the test. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance. During the test, degradation of performance is however allowed.

Criteria C: Temporary loss of function is allowed, provided the functions self recoverable or can be restored by the operation of controls.

☒ **PASS** ☐ **FAIL**

APPENDIX I - PHOTOGRAPHS OF TEST SETUP

LINE CONDUCTED EMISSION TEST (EN 55022)





COMMON MODE CONDUCTED EMISSION TEST



RADIATED EMISSION TEST (EN 55022)





POWER HARMONICS & VOLTAGE FLUCTUATION / FLICKER TEST



ELECTROSTATIC DISCHARGE TEST





RADIATED ELECTROMAGNETIC FIELD TEST



FAST TRANSIENTS/BURST TEST



SURGE IMMUNITY TEST



CONDUCTED DISTURBANCE, INDUCED BY RADIO-FREQUENCY FIELDS TEST



POWER FREQUENCY MAGNETIC FIELD IMMUNITY TEST



VOLTAGE DIPS / INTERRUPTION TEST





APPENDIX II – TEST RESULT OF EN 61000-3-2/-3

Mode 1

Harmonic Emission - IEC 61000-3-2 , EN 61000-3-2 , (EN60555-2)

Comply: IEC 61000-3-2 Ed.2.1 :2001 (incl. Amd.14) - IEC 61000-4-7 Ed.1.0 :1991

ADVANTECH

HARCS Setup File : [unnamed](#)


HARCS Report File : [unnamed](#)

Operator : Ken Jung

EUT : IPC

Model No. IPC-623BP00XB-ES

Remarks MODE: HG2-6400P TEMP:20 HUMD:59



Harmonic Emission - IEC 61000-3-2 , EN 61000-3-2 , (EN60555-2)

2005/1/27 AM 11:04:5

U _{rms} =	230.3	V	P =	189.0	W	THC =	0.110	A	Range:	2 A
I _{rms} =	0.836	A	pf =	0.982		P _{max} =	195.9	W	V-nom:	230 V
									TestTime:	5 min (100%)

IPC

Test completed, Result: PASSED

MODE: HG2-6400P TEMP:20 HUMD:59

BAR-1000 EMC-Printer

Full Bar : Actual Values

Empty Bar : Maximum Values

Blue : Current , Green : Voltage , Red : Failed

**Measurement**

ADVANTECH

Date : 2005/1/27 AM 11:04:5 V3.15

File :

Operator : Ken Jung
EUT : IPC
Model No. IPC-623BP00XB-ES
Remarks MODE: HG2-6400P TEMP:20 HUMD:59

Urms = 230.3V Freq = 49.987 Range: 2 A
Irms = 0.836A Ipk = 1.313A cf = 1.571
P = 189.0W Pap = 192.5VA pf = 0.982
THDi = 13.2 % THDu = 0.10 % Class D

Test - Time : 5min (100 %)

Limit Reference: Pmax = 195.91W

Test completed, Result: PASSED

Order	Freq.	Imax	Imax%	Imax%L	Limit	Status
	[Hz]	[A]	[%]	[%]	[A]	
1	50	1.9852	237.49			
2	100	0.0006	0.0730			
3	150	0.1046	12.515	15.705	0.6661	
4	200	0.0002	0.0292			
5	250	0.0264	3.1542	7.0835	0.3722	
6	300	0.0001	0.0146			
7	350	0.0165	1.9714	8.4116	0.1959	
8	400	0.0001	0.0146			
9	450	0.0034	0.4089	3.4893	0.0980	
10	500	0.0002	0.0292			
11	550	0.0060	0.7155	8.7232	0.0686	
12	600	0.0002	0.0292			
13	650	0.0109	1.2996	18.725	0.0580	
14	700	0.0004	0.0438			



15	750	0.0098	1.1682	19.421	0.0503
16	800	0.0004	0.0438		
17	850	0.0046	0.5549	10.455	0.0444
18	900	0.0002	0.0292		
19	950	0.0103	1.2266	25.830	0.0397
20	1000	0.0004	0.0438		
21	1050	0.0062	0.7447	17.333	0.0359
22	1100	0.0004	0.0438		
23	1150	0.0055	0.6571	16.750	0.0328
24	1200	0.0004	0.0438		
25	1250	0.0040	0.4819	13.352	0.0302
26	1300	0.0002	0.0292		
27	1350	0.0114	1.3581	40.638	0.0279
28	1400	0.0002	0.0292		
29	1450	0.0118	1.4165	45.526	0.0260
30	1500	0.0002	0.0292		
31	1550	0.0077	0.9200	31.607	0.0243
32	1600	0.0002	0.0292		
33	1650	0.0018	0.2190	8.0111	0.0229
34	1700	0.0001	0.0146		
35	1750	0.0022	0.2629	10.196	0.0216
36	1800	0.0002	0.0292		
37	1850	0.0042	0.4965	20.359	0.0204
38	1900	0.0002	0.0292		
39	1950	0.0035	0.4235	18.304	0.0193
40	2000	0.0002	0.0292		

**Mode 6****Harmonic Emission - IEC 61000-3-2 , EN 61000-3-2 , (EN60555-2)**

Comply: IEC 61000-3-2 Ed.2.1 :2001 (incl. Amd.14) - IEC 61000-4-7 Ed.1.0 :1991


ADVANTECHHARCS Setup File : [unnamed](#)HARCS Report File : [unnamed](#)

Operator : Ken Jung

EUT : IPC

Model No. IPC-623BP00XB-ES

Remarks MODE: HP2-6500P TEMP:26 HUMD:51

**Harmonic Emission - IEC 61000-3-2 , EN 61000-3-2 , (EN60555-2)**

2005/1/26 PM 11:28:2

U _{rms} =	230.3	V	P =	179.8	W	THC =	0.112	A	Range:	2 A
I _{rms} =	0.823	A	pf =	0.948		P _{max} =	181.1	W	V-nom:	230 V
									TestTime:	5 min (100%)

IPC

Test completed, Result: PASSED

MODE: HP2-6500P TEMP:26 HUMD:51

BAR-1000 EMC-Print

Full Bar : Actual Values

Empty Bar : Maximum Values

Blue : Current , Green : Voltage , Red : Failed

**Measurement**

ADVANTECH

Date : 2005/1/26 PM 11:23:2 V3.15

File :

Operator : Ken Jung
EUT : IPC
Model No. IPC-623BP00XB-ES
Remarks MODE: HP2-6500P TEMP:26 HUMD:51

Urms = 230.3V Freq = 49.987 Range: 2 A
Irms = 0.823A Ipk = 1.326A cf = 1.611
P = 179.8W Pap = 189.6VA pf = 0.948
THDi = 13.6 % THDu = 0.10 % Class D

Test - Time : 5min (100 %)

Limit Reference: Pmax = 181.08W

Test completed, Result: PASSED

Order	Freq. [Hz]	Imax [A]	Imax% [%]	Imax%L [%]	Limit [A]	Status
1	50	0.8204	99.659			
2	100	0.0010	0.1186			
3	150	0.1085	13.182	17.627	0.6157	
4	200	0.0004	0.0445			
5	250	0.0034	0.4152	0.9935	0.3440	
6	300	0.0002	0.0297			
7	350	0.0139	1.6904	7.6851	0.1811	
8	400	0.0005	0.0593			
9	450	0.0039	0.4745	4.3144	0.0905	
10	500	0.0006	0.0741			
11	550	0.0105	1.2752	16.564	0.0634	
12	600	0.0001	0.0148			
13	650	0.0070	0.8452	12.975	0.0536	
14	700	0.0005	0.0593			



15	750	0.0137	1.6607	29.417	0.0465
16	800	0.0002	0.0297		
17	850	0.0134	1.6311	32.744	0.0410
18	900	0.0004	0.0445		
19	950	0.0044	0.5338	11.977	0.0367
20	1000	0.0005	0.0593		
21	1050	0.0061	0.7414	18.385	0.0332
22	1100	0.0002	0.0297		
23	1150	0.0063	0.7711	20.942	0.0303
24	1200	0.0002	0.0297		
25	1250	0.0027	0.3262	9.6304	0.0279
26	1300	0.0005	0.0593		
27	1350	0.0043	0.5190	16.547	0.0258
28	1400	0.0001	0.0148		
29	1450	0.0046	0.5635	19.296	0.0240
30	1500	0.0004	0.0445		
31	1550	0.0028	0.3410	12.485	0.0225
32	1600	0.0002	0.0297		
33	1650	0.0029	0.3559	13.868	0.0211
34	1700	0.0002	0.0297		
35	1750	0.0017	0.2076	8.5799	0.0199
36	1800	0.0004	0.0445		
37	1850	0.0029	0.3559	15.549	0.0188
38	1900	0.0002	0.0297		
39	1950	0.0043	0.5190	23.901	0.0179
40	2000	0.0002	0.0297		

**Mode 1**

ADVANTECH

Date : 2005/1/27 AM 11:17:2 V3.15

File :

Operator : Ken Jung
EUT : IPC
Model No. IPC-623BP00XB-ES
Remarks MODE: HG2-6400P TEMP:26 HUMD:55

Urms = 230.3V Freq = 49.987 Range: 2 A
Irms = 0.835A Ipk = 1.304A cf = 1.561
P = 188.8W Pap = 192.3VA pf = 0.982

Test - Time : 1 x 10min = 10min (100 %)

LIN (Line Impedance Network) : SLIN 0.24ohm +j0.15ohm N:0.16ohm +j0.10ohm

Limits : Plt : 0.65 Pst : 1.00
dmax : 4.00 % dc : 3.30 %
dtLim: 3.30 % dt>Lim: 500ms

Test completed, Result: PASSED

Plt = 0.072

	Pst	dmax	dc	dt>Lim	Fail
		[%]	[%]	[ms]	
1	0.072	0.000	0.010	0.000	



ADVANTECH

Date : 2005/1/27 AM 11:30:1 V3.15

File :

Operator : Ken Jung
EUT : IPC
Model No. IPC-623BP00XB-ES
Remarks MODE: HG2-6400P TEMP:26 HUMD:55

Urms = 230.3V Freq = 49.987 Range: 2 A
Irms = 0.834A Ipk = 1.306A cf = 1.566
P = 188.3W Pap = 192.1VA pf = 0.981

Test - Time : 1 x 10min = 10min (100 %)

LIN (Line Impedance Network) : SLIN 0.24ohm +j0.15ohm N:0.16ohm +j0.10ohm

Limits : Plt : 0.65 Pst : 1.00
dmax : 4.00 % dc : 3.30 %
dtLim: 3.30 % dt>Lim: 500ms

Test completed, Result: PASSED

Plt = 0.083

	Pst	dmax	dc	dt>Lim	Fail
		[%]	[%]	[ms]	
1	0.083	0.210	0.100	0.000	

**Mode 6**

ADVANTECH

Date : 2005/1/27 AM 10:05:2 V3.15

File :

Operator : Ken Jung
EUT : IPC
Model No. IPC-623BP00XB-ES
Remarks MODE: HP2-6500P TEMP:26 HUMD:55

Urms = 230.3V Freq = 49.987 Range: 2 A
Irms = 0.821A Ipk = 1.313A cf = 1.598
P = 179.4W Pap = 189.1VA pf = 0.948

Test - Time : 1 x 10min = 10min (100 %)

LIN (Line Impedance Network) : SLIN 0.24ohm +j0.15ohm N:0.16ohm +j0.10ohm

Limits : Plt : 0.65 Pst : 1.00
dmax : 4.00 % dc : 3.30 %
dtLim: 3.30 % dt>Lim: 500ms

Test completed, Result: PASSED

Plt = 0.072

	Pst	dmax	dc	dt>Lim	Fail
		[%]	[%]	[ms]	
1	0.072	0.000	0.010	0.000	



ADVANTECH

Date : 2005/1/27 AM 10:17:0 V3.15

File :

Operator : Ken Jung
EUT : IPC
Model No. IPC-623BP00XB-ES
Remarks MODE: HP2-6500P TEMP:26 HUMD:55

Urms = 230.3V Freq = 49.987 Range: 2 A
Irms = 0.823A Ipk = 1.325A cf = 1.610
P = 179.7W Pap = 189.6VA pf = 0.948

Test - Time : 1 x 10min = 10min (100 %)

LIN (Line Impedance Network) : SLIN 0.24ohm +j0.15ohm N:0.16ohm +j0.10ohm

Limits : Plt : 0.65 Pst : 1.00
dmax : 4.00 % dc : 3.30 %
dtLim: 3.30 % dt>Lim: 500ms

Test completed, Result: PASSED

Plt = 0.078

	Pst	dmax	dc	dt>Lim	Fail
		[%]	[%]	[ms]	
1	0.078	0.000	0.070	0.000	