

21.5" WebPanel WPC002-215NAT



- 21.5" brilliant TFT-LCD graphic display, 1920 x 1080
- Without touch
- IP65 front, flush frame design
- Integrated WiFi and Bluetooth
- Fanless design

<https://www.wachendorff-electronics.com/WPC002-215NAT>

Description

The Series 1 WebPanels with the RK3399 chipset are available in sizes from 10.1" to 23.8" and can be equipped with either a projected capacitive, resistive or no touchscreen. Particularly noteworthy is the especially flat front frame, which enables almost aligned mounting in the panel cut-out.

The RK3399 chipset has a quad-core Cortex-A53 with up to 1.4 GHz and dual-core Cortex-A72 with 1.8 GHz. The housings are IP65 rated at the front and have a very compact and robust design thanks to the specially designed aluminium housing. The low installation depth means that the displays can be used almost anywhere.

Product details

Power supply:	Hollow connector 5.5 x 2.5 mm: 12 VDC to 36 VDC Screw terminal: 12 VDC to 36 VDC
Power consumption:	Typical power consumption: 18 W Maximum power consumption: 48 W
Display:	21.5" TFT-LCD
Resolution:	1920 x 1080 Pixel
Aspect ratio:	16:9
Brightness:	300 cd/m ² 1000 cd/m ² (High Brightness) 800 cd/m ² (High Brightness WT)
Colours:	16,7 M.
Viewing angle:	89/89/89/89 (L/R/U/D)
Touchscreen:	without Touch
Glas hardness:	7H
Processor:	RK3399-Quad-Core Chip Dual Core Cortex-A53 up to 1.4 GHz Quad-Core Cortex-A72 up to 1.8 GHz
RAM:	4 GB DDR3 RAM
Storage:	Onboard 64 GB eMMC NAND Flash

I/O-ports:	USB: 1x USB 3.0 Typ A, 1x USB 2.0 Typ A Serial DB9: 1x RS-232 12-pin screw terminal: 1x RS-485, 1x RS-232, 1x TTL, 3x GPIO Ethernet: 1x 10/100/1000 BaseT(X), RJ45, galvanically isolated Display: 1x HDMI-output Audio output: 3.5 mm jack Memory card slot: microSD-Slot Sim card slot: Standard SIM (without function as standard) WLAN: 1x 802.11 a/b/g/n/ac/ax Bluetooth: 1x Bluetooth 5.0
Housing:	Robust aluminium housing
Mounting:	VESA 75 x 75, VESA 100 x 100 Panel mount
Protection class:	IP65 at the front
Weight:	Approx. 5.8 kg
Dimensions (WxHxD):	557 mm x 345 mm x 63 mm
Environmental conditions:	Operation: -10 °C to +60 °C Optional WT: -20 °C to +70 °C High Brightness : 0 to +50 High Brightness WT: -20 °C to +70 °C Storage: -20 °C to +70 °C 95 %, non-condensing
Certifications:	CE FCC Class A CCC
Operating system:	Android Android + AutomationBrowser (standard, for SAIA visualisations on request)
Packing list:	1x device 1x mounting material
Tariff number:	84714100
Manufacturer:	Wachendorff Prozesstechnik

Products Order no.

WPC002-215NAT04064AAV02P- 21.5" web panel, without touch, A automation browser.


WPC002-215NAT04064AAV02P 21.5" web panel, without touch.

Accessories Order no.

PPC-PWRCRD_01	Mains cable / connection cable E+F CEE 7/7 to C13 1.5 m
WPC- PWRADAP_24VDC2.5A	External power supply unit for WebPanel, 230 VAC to 24 VDC with hollow connector and C14 plug
PPC-WALL-VESA-01	VESA wall mount metal, 75 x 75, 100 x100, black, including screw accessory pack
PPC-Stand_01	Industrial monitor/display stand, VESA 100x100, black
PPC-Stand_02	Industrial monitor/display stand, VESA 100x100, silver

Drawings

Drawings (mm):





Wachendorff Prozesstechnik GmbH & Co. KG
Industriestrasse 7 • 65366 Geisenheim
Germany

Phone: +49 (0) 67 22 / 99 65 - 20
E-Mail: wp@wachendorff.de
www.wachendorff-prozesstechnik.de

